

Contents

1	Introduction	1
2	Carbon in silicon: properties and industrial interests	5
2.1	Industrial interest: from an impurity to a dopant	6
2.1.1	HBT SiGeC technology	6
2.1.2	Reduction of the strain	7
2.1.3	Reduction of boron diffusion	8
2.2	Carbon close to the thermodynamical equilibrium	9
3	Dopant diffusion in silicon	12
3.1	Theory of diffusion in semiconductors	12
3.1.1	Continuum theory	12
3.1.2	Additional effects on diffusion	14
3.1.3	Atomistic theory of diffusion	16
3.1.4	Diffusion mechanisms in semiconductors	19
3.2	Solving diffusion equations	21
3.3	Diffusion under non-equilibrium conditions	22
3.4	Silicon self-diffusion	23
4	Experimental methods	27
4.1	Cleaning procedure	28
4.2	Molecular Beam Epitaxy	29
4.3	Annealing	32
4.4	Secondary Ion Mass Spectrometry	33
4.5	Electrochemical capacitance-voltage profiler	35
4.6	Other tools	36
5	Carbon incorporation in silicon	38
5.1	Theory of growth	38
5.1.1	Elastic relaxation during growth	39
5.1.2	Plastical relaxation during growth	40
5.1.3	Concept of surface solubility	42
5.2	Incorporation of high carbon concentration	42

5.2.1	Phase diagram	43
5.2.2	Below 500°C	44
5.2.3	Intermediate temperatures	45
5.2.4	High temperatures	48
5.3	Conclusions	49
6	Carbon out-diffusion and its influence on dopant diffusion	52
6.1	Diffusion of high carbon concentrations	53
6.2	Simulation parameters	55
6.3	Engineering dopant diffusion by carbon incorporation	57
6.3.1	Boron	58
6.3.2	Antimony	59
6.4	Overview about C out-diffusion	64
7	Precipitation	68
7.1	Basic issues	68
7.1.1	SiC properties in Si	68
7.1.2	SiC precipitation mechanisms	69
7.2	Observations of C precipitation	71
8	Lattice engineering	75
8.1	Motivation	75
8.2	Basic issues	76
8.2.1	Lattice mismatch	76
8.2.2	Fabrication approach	78
8.2.3	Results	79
8.3	Outlook	80
9	Conclusions	82
10	Conclusions in German - Zusammenfassung	84
A	In-plane segregation	87
B	C diffusion and additional SIMS profiles	89
C	Strain during pseudomorphic growth and Matthews-Blackeslee criterium	92
	Bibliography	94