

Contents

<i>Abstract</i>	<i>vii</i>
<i>Zusammenfassung</i>	<i>ix</i>
<i>Acknowledgments</i>	<i>xi</i>
<i>Acronyms</i>	<i>xvii</i>
<i>1 Introduction</i>	<i>1</i>
<i>1.1 Motivation</i>	<i>3</i>
<i>1.2 Focused research problems</i>	<i>6</i>
<i>1.3 Structure of the thesis</i>	<i>8</i>
<i>2 Digitalisation concepts</i>	<i>11</i>
<i>2.1 Smart Systems</i>	<i>11</i>
<i>2.2 3D information modelling: BIM and 3D GIS</i>	<i>12</i>

2.3	<i>Internet of Things (IoT) and digital twin</i>	15
2.4	<i>Gameful Design</i>	16
2.5	<i>Virtual Reality and immersive technologies</i>	18
3	<i>Immersive 3D planning of total station networks</i>	23
3.1	<i>Brief history: 2D network design</i>	24
3.2	<i>State of the art: 2.5D network design</i>	26
3.3	<i>Challenges for the design of monitoring installations</i>	30
3.4	<i>Motivation for an object orientated 3D approach</i>	33
3.5	<i>Software realisation: VRsurv</i>	36
3.5.1	<i>Design with Unity</i>	37
3.5.2	<i>Data Templates</i>	39
3.5.3	<i>Usage of Virtual Reality</i>	40
3.5.4	<i>Related work: 3D instrument simulation</i>	43
3.6	<i>Implemented 3D Quality checks in VRsurv</i>	44
3.6.1	<i>Collision control</i>	44
3.6.2	<i>Set-up stability due to direct sun exposure</i>	47
3.6.3	<i>Orientation of prisms</i>	50
3.6.4	<i>Interferences caused by adjacent prisms</i>	55
3.6.5	<i>Visualisation of confidence ellipsoids</i>	60
3.7	<i>Use case: Tunnel monitoring with total stations</i>	62
3.7.1	<i>Task description and requirements</i>	62
3.7.2	<i>Console design and placement of the total station</i>	64
3.7.3	<i>Prism configuration and automatic target aiming</i>	66
3.7.4	<i>Results of the feasibility study</i>	67
3.8	<i>Conclusion</i>	68
3.8.1	<i>Improvements</i>	68
3.8.2	<i>Limitations</i>	69
3.8.3	<i>Future work</i>	70
4	<i>Smart total station monitoring</i>	71
4.1	<i>State of the art: Monitoring with total stations</i>	72

4.1.1	Commercial monitoring solutions	72
4.1.2	Customised monitoring solutions	74
4.2	Challenges for state-of-the-art systems	75
4.3	Enhanced total station monitoring for complex sites	76
4.4	Smart prism objects	79
4.5	Avoidance of local atmospheric disturbances	82
4.5.1	Air-conditioning devices and total station monitoring	82
4.5.2	Atmospheric experiments on the roof of Graz University of Technology	83
4.5.3	Experimental digital twin application with the Unity software	86
4.5.4	Outlook: dynamic temperature acquisition with mobile platforms	87
4.6	Temporary obstruction of the line of sight	88
4.7	Conclusion	91
4.7.1	Improvements	91
4.7.2	Limitations	93
4.7.3	Future work	94
5	Immersive data visualisation with Virtual Reality	95
5.1	Brief history: from sculptures to 2D displays	96
5.2	State of the art: Conventional 2.5D viewers	98
5.3	Challenges for conventional 2.5D viewers	98
5.4	Motivation for the usage of Virtual Reality	101
5.5	Hardware development of Virtual Reality devices	103
5.6	The role of VR applications in engineering geodesy	106
5.6.1	Visualisation of 3D models and point clouds	106
5.6.2	Comprehensive multi-dimensional data investigation	107
5.6.3	Digitalisation and data filtering	112
5.6.4	Education	114
5.7	Outlook: Collaboration	117
5.8	Conclusion	118

5.8.1	<i>Improvements</i>	118
5.8.2	<i>Limitations</i>	119
5.8.3	<i>Future work</i>	120
6	<i>Summary and Discussion</i>	121
6.1	<i>Quality improvement</i>	122
6.2	<i>Discussion: Connected 3D environments</i>	123
6.3	<i>Conclusion (Surveyor 4.0)</i>	125
6.4	<i>Main scientific contributions</i>	127