

# Contents

|                                                                             |           |
|-----------------------------------------------------------------------------|-----------|
| <b>List of Symbols</b>                                                      | <b>v</b>  |
| <b>1 Introduction</b>                                                       | <b>1</b>  |
| <b>2 Literature review</b>                                                  | <b>7</b>  |
| 2.1 Total Pressure Loss in Compressor Bleed Air Systems . . . . .           | 7         |
| 2.1.1 1D-Flow Solver: Assumptions and Correlations . . . . .                | 7         |
| 2.1.1.1 Off-take . . . . .                                                  | 10        |
| 2.1.1.2 Manifold . . . . .                                                  | 15        |
| 2.1.1.3 Exit tube . . . . .                                                 | 18        |
| 2.1.2 Complete System, Component Interaction, and Three-dimensional Effects | 19        |
| 2.2 Interaction with the Compressor Main Gas Path . . . . .                 | 23        |
| 2.2.1 Uniform Bleed . . . . .                                               | 23        |
| 2.2.2 Non-uniform Bleed . . . . .                                           | 27        |
| 2.3 Objectives and Structure of the Present Investigation . . . . .         | 29        |
| <b>3 Experimental methods</b>                                               | <b>33</b> |
| 3.1 Test Rig Infrastructure . . . . .                                       | 33        |
| 3.2 Test Section Conception . . . . .                                       | 34        |
| 3.2.1 Guide Vanes . . . . .                                                 | 36        |
| 3.2.2 Off-take Design . . . . .                                             | 37        |
| 3.2.3 Manifold and Exit Tubes . . . . .                                     | 38        |
| 3.3 Test Section Instrumentation . . . . .                                  | 40        |
| 3.3.1 Manifold measurements . . . . .                                       | 42        |
| 3.3.2 Vane passage measurements . . . . .                                   | 43        |
| <b>4 Numerical Method</b>                                                   | <b>49</b> |
| 4.1 Domain Modelling . . . . .                                              | 49        |
| 4.1.1 Grid Generation . . . . .                                             | 52        |
| 4.1.2 Turbulence Model . . . . .                                            | 54        |
| 4.1.3 Boundary Conditions . . . . .                                         | 54        |
| 4.1.4 Sensitivity Study . . . . .                                           | 55        |

|          |                                                                                                       |           |
|----------|-------------------------------------------------------------------------------------------------------|-----------|
| 4.1.5    | Solver and Simulation . . . . .                                                                       | 57        |
| 4.2      | Data Post-processing . . . . .                                                                        | 57        |
| 4.3      | Validation of the Simulations . . . . .                                                               | 59        |
| 4.3.1    | 20° Vane No Bleed Slot . . . . .                                                                      | 61        |
| 4.3.2    | 20° Vane with 45° Slot and Four Exit Tubes at $br = 9\%$ . . . . .                                    | 63        |
| <b>5</b> | <b>Results and Discussion</b>                                                                         | <b>71</b> |
| 5.1      | Influence of the Exit Tube Configuration and Slot Geometry on Total Pressure Losses . . . . .         | 72        |
| 5.1.1    | Total Pressure Loss in the System Components . . . . .                                                | 73        |
| 5.1.2    | Slot Flow Specificities . . . . .                                                                     | 77        |
| 5.1.3    | Manifold Flow Specificities . . . . .                                                                 | 81        |
| 5.1.3.1  | Manifold Static Pressure Distribution . . . . .                                                       | 82        |
| 5.1.3.2  | Manifold Velocity Field . . . . .                                                                     | 89        |
| 5.1.3.3  | Mass Flow Distribution in the Manifold . . . . .                                                      | 91        |
| 5.1.4    | Total Pressure Loss Generation in the Manifold . . . . .                                              | 96        |
| 5.1.4.1  | Flow Topology and Swirl Tube Analogy . . . . .                                                        | 96        |
| 5.1.4.2  | Total Pressure Loss on the Positive Stream . . . . .                                                  | 100       |
| 5.1.4.3  | Total Pressure Loss on the Backflow Stream . . . . .                                                  | 103       |
| 5.1.5    | Exit Tube Flow . . . . .                                                                              | 111       |
| 5.1.5.1  | Total Pressure Loss Generation in the Exit Tube . . . . .                                             | 112       |
| 5.1.5.2  | Comparison with 1D network Correlations . . . . .                                                     | 115       |
| 5.2      | Influence of the Vane Aerodynamic Loading on Total Pressure Losses . . . . .                          | 119       |
| 5.2.1    | Total Pressure Loss in the System Components . . . . .                                                | 119       |
| 5.2.2    | Slot Flow Specificities . . . . .                                                                     | 121       |
| 5.2.3    | Manifold Flow Specificities . . . . .                                                                 | 122       |
| 5.2.3.1  | Manifold Static Pressure Distribution . . . . .                                                       | 123       |
| 5.2.3.2  | Manifold Velocity Field . . . . .                                                                     | 125       |
| 5.2.3.3  | Mass Flow Distribution in the Manifold . . . . .                                                      | 126       |
| 5.3      | Bleeding Non-uniformity . . . . .                                                                     | 129       |
| 5.3.1    | Influence of the Exit Tube Configuration and Slot Geometry on the Main Gas Path Interaction . . . . . | 130       |
| 5.3.2    | Influence of the Vane Aerodynamic Loading on the Main Gas Path Interaction . . . . .                  | 134       |

---

|       |                                                                                  |     |
|-------|----------------------------------------------------------------------------------|-----|
| 5.4   | Onset and Development of Backflow . . . . .                                      | 137 |
| 5.4.1 | Modelling of Backflow Onset and Development . . . . .                            | 137 |
| 5.4.2 | Influence of the Vane and Slot Configuration on the Backflow Onset . .           | 143 |
| 6     | Conclusion                                                                       | 149 |
|       | Bibliography                                                                     | 153 |
|       | Appendix                                                                         | 165 |
| A.1   | Wedge Probe Calibration . . . . .                                                | 165 |
| A.2   | Manifold Flow Field Description . . . . .                                        | 171 |
| A.3   | Swirl Tube Analogy . . . . .                                                     | 172 |
| A.4   | Turbulence Kinetic Energy with the 90° Slot Configuration . . . . .              | 174 |
| A.5   | Exit Tube Recirculation with the 20° Vane Configuration . . . . .                | 175 |
| A.6   | Exit Tube Recirculation with the 10° Vane Configuration . . . . .                | 177 |
| A.7   | Turbulence Kinetic Energy with the 45° Slot and both Exit Tube Configurations    | 180 |
| A.8   | Bleeding Non-uniformity for the 90° Slot with the 10° Vane . . . . .             | 183 |
| A.9   | Slot Flow Interaction with a Single Exit Tube for the 90° Slot with the 20° Vane | 184 |