

Contents

1	Introduction and Motivation	1
1.1	GSM Mobile Phone Localization	1
1.2	Localization in Search and Rescue Scenarios	4
1.3	Key Inventive Concept	5
1.4	Scope of this Work	6
2	Basic System Architecture and Measurement Setup	7
2.1	Time Difference of Arrival Localization Systems	7
2.1.1	Localization Scenario	7
2.1.2	Major Challenges and Requirements	9
2.1.3	Auxiliary System Components	10
2.2	Time Difference of Arrival Estimation Scenario	12
2.2.1	Elementary Measurement Setup	12
2.2.2	Generic Radio Channel Model	14
3	GSM Signal Characteristics and Modeling	17
3.1	Physical Layer Structure	17
3.1.1	Modulation	17
3.1.2	Burst Types and Structures	20
3.1.3	Power and Spectral Characteristics	22
3.1.4	Multiple Access and Duplexing	24
3.2	Modeling of GSM Signals	29
3.2.1	Single Burst Signal Model	29
3.2.2	Frequency Hopping Signal Model	30
4	Coherent Wideband Signal Acquisition and Modeling	31
4.1	Wideband Signal Acquisition Techniques	31
4.1.1	Wideband Frontend Signal Acquisition	31
4.1.2	Narrowband Frontend Signal Acquisition	33
4.1.3	Mixed Acquisition Schemes	35
4.1.4	Coherence and Phase Relationships	36
4.2	Properties of Acquired Wideband Signals	37
4.2.1	Frequency Hopping Bandwidth	37
4.2.2	Effective Signal Bandwidth	37
4.2.3	Signal to Noise Ratio	38

4.3	Pre-Processing and Multiple Source Separation	40
4.3.1	Burst Isolation Technique	40
4.3.2	Wideband Signal Reconstruction Technique	43
4.3.3	Multiple Source Separation Technique	44
5	Coherent Time Difference of Arrival Estimation Techniques	45
5.1	Wideband Crosscorrelation Technique	45
5.1.1	Definition of the Crosscorrelation Function	45
5.1.2	Decomposition of the Crosscorrelation Function	46
5.1.3	Ambiguity Function of Frequency Hopping Signals	47
5.1.4	Shape of the Ambiguity Function	48
5.1.5	Properties of the Ambiguity Function	56
5.1.6	Application of Concatenated and Stacked Signals	60
5.1.7	Range Limitations	64
5.2	Burst Phase Analysis Technique	66
5.2.1	Derivation for Simple Delay Scenarios	66
5.2.2	Evaluation of Multiple Burst Signals	68
5.2.3	Influence of Multipath Components	71
5.2.4	Averaging of Burst Phase Differences	77
5.2.5	Range Ambiguities	80
5.3	Realizable Frequency Hopping Signal Configurations	81
6	Numerical Performance Simulation and Evaluation	83
6.1	Simulation Environment and Parameters	83
6.2	Noise Performance in Multipath-Free Scenarios	86
6.2.1	AWGN Channel Model	86
6.2.2	Cramér-Rao Lower Bound	86
6.2.3	Estimation Standard Deviation	87
6.3	Multipath Performance in Two-Paths Scenarios	92
6.3.1	Two-Path Channel Model	92
6.3.2	Maximum Estimation Bias	92
6.4	Multipath Performance in Realistic Scenarios	96
6.4.1	Tapped Delay-Line Channel Model	96
6.4.2	Resolvability of Propagation Paths	100
6.5	Summary of Estimation Technique Performance	104
7	Prototype System Structure and Measurement Results	105
7.1	Structure of the Receiving Stations	105
7.1.1	Main Functional Components	105
7.1.2	Synchronization Source Module	106
7.1.3	Synchronization and Trigger Module	107
7.1.4	Wideband Signal Acquisition Module	109
7.1.5	Data and Control Module	111
7.1.6	Integration of the Modules	112

7.2	Characteristics of Hardware Modules	113
7.2.1	Phase Noise Profile of Synchronization Signals	113
7.2.2	Synchronicity of Synchronization Source Signals	114
7.2.3	Synchronicity of Synchronization and Trigger Signals	116
7.2.4	Frequency Response of Wideband Signal Acquisition Modules	118
7.2.5	Symmetry of Wideband Signal Acquisition Modules	120
7.3	Time Difference of Arrival Measurement Results	122
7.3.1	Static Offset Compensation Procedure	122
7.3.2	Measurement Setup and Evaluation Procedure	123
7.3.3	Originating GSM Signal Configuration	126
7.3.4	Delay-Line Measurement Results	126
7.4	Summary of Hardware and Measurement Results	130
8	Summary and Outlook	133
8.1	Major Achievements and Contributions	133
8.2	Future Work and Development	134
8.3	Patents, Scientific Publications and Theses	137
	Appendices	139
A	Frequency Hopping Sequence Generation in GSM Systems	141
B	Logical and Physical Channels in GSM Systems	143
B.1	Definition of Resources and Channels	143
B.2	Structure of the 26-Multiframe	143
B.3	Structure of the 51-Multiframe	144
C	Frequency Hopping Signal Transmission Initiation in GSM Systems	147
C.1	Requirements for Signal Transmission Initiation	147
C.2	Voice and Data Connection	147
C.3	Modified Handover Procedure	150
D	Time Difference of Arrival Estimation for Narrowband GSM Signals	153
D.1	Narrowband Crosscorrelation Technique	153
D.2	Model-based Estimation Techniques	155
D.3	Incoherent Integration with Multipath Rejection Technique	156
D.4	Successive Cancellation Technique	158
D.5	Further Applicable Techniques	159
D.6	Comparative Summary	162
E	Localization System Architecture for Search and Rescue Scenarios	163
	References	165