

Contents

Introduction — 1

1 Magnetic fields of axially symmetrical magnetic systems used for generation of the strong fields (methods of calculation, assessment of the edge effects) — 8

- 1.1 Magnetic field of the systems with the given current distribution — 8
- 1.2 The setting of the task for the calculation of a magnetic field at a small penetration depth — 13
- 1.3 The determination of the parameters of the inductor systems at a strongly-pronounced skin effect according to the simplified field pattern — 18
 - 1.3.1 The field of single-turn solenoids (flat ring) above the ideally-conducting plane ($h \ll r_1$) — 18
 - 1.3.2 The field of multiwinding solenoid in the form of a flat spiral above the plane (Figure 1.6b) — 19
 - 1.3.3 Field of solenoid in off-loading cylindrical screens — 20
- 1.4 Edge effects in single-coil magnets. Modelling of problems — 21
- 1.5 References — 27

2 Calculating formulas and the results of numerical estimations of field parameters for typical single-turn magnets — 29

- 2.1 The field of the flat ring as an example of the single-turn magnet with sharply pronounced edge effect — 29
- 2.2 The coil of a rounded cross-section (an ideally conductive toroid) — 32
- 2.3 Thin-wall single-turn magnets — 35
- 2.4 The field of rectangular coils with arbitrary ratios of characteristic dimensions — 39
- 2.5 Induction of the one-turn magnet placed near the coaxial cylinder or the plane — 41
- 2.6 References — 44

3 Field diffusion into the conductors and their heating — 45

- 3.1 Adiabatic heating of conductors at a given current density — 46
- 3.2 Linear regime of field diffusion in conductors — 50

3.3	The surface impedance. Energy losses in the skin layer with sinusoidal current — 52
3.4	The asymptotical values of the magnetic field intensity and current density at the conductor edge under the condition of a pronounced skin effect — 57
3.5	Examples of the diffusion of the uniform pulse electromagnetic field into a medium with constant conductivity — 61
3.6	Energy generation and heating a medium in the case of diffusion of the pulse magnetic field into the conductor — 65
3.7	Heating of a conductor with a current in an external magnetic field — 70
3.8	Minimization of a uniform medium heating under diffusion of the pulse magnetic field — 76
3.9	One-dimensional diffusion of the field into a medium with conductivity depending on the coordinate. Reduction of energy generation in the surface layer — 78
3.10	One-dimensional nonlinear diffusion of the magnetic field into the conductor heated by the eddy current — 81
3.11	Approximate description of the surface effect. “The skin layer method” — 85
3.12	References — 89
4	Matching of the parameters of solenoids and power supply sources — 91
4.1	General requirements to the power supply source — 91
4.2	Optimization of the parameters of the system of solenoids – capacity energy storage — 92
4.3	Optimization of solenoids according to Fabri — 94
4.4	Transformations of energy in a circuit with alternating inductance — 98
4.4.1	Direct current in the element of the electrical circuit with alternating inductance — 99
4.4.2	Energy transformations in the short-circuiting coil with alternating inductance — 99
4.4.3	Railgun powered by energy capacity storage — 100
4.5	On the application of inductive storages for supplying the magnetic systems — 109
4.6	References — 112

5	Electromagnetic forces and mechanical stresses in multiturn solenoids. The optimization of multilayered windings — 113
5.1	Asimuthal and axial stresses in the thin-wall turn in the poloidal magnetic field — 114
5.2	Mechanical stresses in the uniform cylinder with a given current distribution — 117
5.2.1	A winding with constant current density — 118
5.2.2	A winding with a current density decreasing inversely with radius (Bitter's solenoid) — 120
5.3	Mechanical stresses in an equilibrium thin-wall cylinder with current — 121
5.4	Mechanical stresses in two-component winding — 125
5.5	Magnets with mechanically separated thin current layer. Series or parallel connection of layers — 129
5.5.1	A winding with a series connection of current layers — 129
5.5.2	A winding with parallel-connected layers — 130
5.6	Multilayer magnet with equally-loaded winding — 131
5.7	Multilayer magnets with equally-loaded internal reinforcements — 136
5.8	The plastic deformation and the resource of multiturn magnets — 140
5.9	References — 145
6	Generation of strong magnetic fields in multiturn magnets — 147
6.1	Traditional constructions of solenoids with spiral multilayer windings — 149
6.2	Present-day materials used to make windings — 154
6.3	Special features of constructions of present-day multiturn monolithic magnets with field of 60–80 T — 159
6.4	The results of tests of multiturn magnets and investigation of their destruction — 164
6.5	Magnets with record fields — 169
6.6	Flat helical solenoids — 175
6.7	References — 178
7	Solenoids with quasi-force-free windings — 182
7.1	Quasi-force-free configurations, an analog of which is a winding of a quasi-force-free magnet — 183
7.1.1	One-dimensional quasi-force-free magnetic systems: the flat layer and cylinder — 183

7.1.2	Two-dimensional force-free configurations satisfying the characteristic boundary conditions —	186
7.1.3	Features of current distribution in the face zone of a force-free magnet —	192
7.2	The methods of realization of a quasi-force-free winding. The estimates of residual mechanic stresses in a thin-wall quasi-force-free winding —	194
7.2.1	Quasi-force-free winding with pairs of the equilibrium current layers (number of pairs $N \gg 1$) —	194
7.2.2	Multilayer magnetic systems with variable direction of current in each layer —	196
7.3	Configurations of magnetic systems with equilibrium windings with zero thickness —	201
7.3.1	One-modular configurations —	202
7.3.2	Multimodular systems —	206
7.4	Thin-wall quasi-force-free magnets with current removals —	210
7.4.1	Systems with equally-loaded internal reinforcements —	210
7.5	Comparative estimates of the residual stresses and sizes of magnets with a quasi-force-free winding and loaded outer zone —	213
7.6	Design methods of quasi-force-free magnets —	214
7.7	References —	217
8	Generation of strong pulsed magnetic fields in single-turn magnets. Magnetic systems for the formation of pulsed loads —	219
8.1	Mechanical stresses in a single-turn magnet operating under the condition of a sharply pronounced skin effect —	220
8.2	Assessing the strength of single-turn magnets at short pulses —	222
8.3	Thermoelastic stresses in single-turn magnets —	227
8.4	The destruction of single-turn magnets. The problem of erosion —	231
8.5	Special construction features of single-turn magnets and their power supplies —	237
8.6	Deformed single-turn magnets restored after the discharge —	246
8.7	Magnetic systems used for deformation of solids and the study of their properties —	247
8.8	Magnetic systems for the acceleration of conductors —	259
8.9	References —	266

- 9 Generation of ultrahigh magnetic fields in destructive single-turn magnets — 270**
 - 9.1 Physical processes accompanying the generation of megagauss magnetic field in single-turn magnets — 270
 - 9.2 Modeling problems illustrating the role of different factors leading to the destruction of single-turn magnets — 281
 - 9.3 Hydrodynamic flows in single-turn solenoids. Application of the model of a noncompressible liquid with ideal conductivity to the description of the deformation of a thick-wall turn — 283
 - 9.4 Electrical explosion of turns of small thickness. Evaluation of the induction achieved in the destruction of turns with small initial dimensions — 291
 - 9.5 One-dimensional hydrodynamic flow in the wall of a single-turn magnet. Shock wave in conductors initiated by superstrong magnetic fields — 298
 - 9.6 General information on the electric explosion of conductors — 301
 - 9.7 Electric explosion of the skin layer in superhigh magnetic fields. Ideal model — 311
 - 9.8 The actual processes developing for “slow” and “fast” electric explosions of a conductor surface skin layer in a superhigh magnetic field — 313
 - 9.9 Computer simulation of a skin layer explosion — 320
 - 9.10 References — 330
- 10 Magnetic cumulation — 333**
 - 10.1 Initial idea. Brief history. Main trends in development and research — 333
 - 10.2 MC energy generators — 336
 - 10.3 Physical processes in magnetic cumulation. Analytical estimates for the MC-1 system — 342
 - 10.3.1 Induction amplitude and the radius of turnaround for flux compression by an ideal cylindrical shell — 343
 - 10.3.2 Estimation of the pulse duration of a magnetic field in magnetic cumulation — 344
 - 10.3.3 The effect of field diffusion on the induction amplitude with magnetic cumulation — 346
 - 10.3.4 Restrictions on the induction amplitude conditioned by the compressibility of a medium — 349
 - 10.3.5 Violation of the stability of a liner at flux compression — 352

10.4	Flux compression systems not using the explosion energy for liner acceleration — 355
10.4.1	MDC systems with azimuth current in a liner — 357
10.4.2	Magnetodynamic cumulation in a Z-θ pinch system — 362
10.5	Analytical estimations and simulation of magnetodynamic cumulation — 365
10.6	Explosion devices and solenoids of an initial field used in magnetic cumulation — 379
10.6.1	Detonation of the explosive charge — 379
10.6.2	Generation of the initial magnetic field — 382
10.7	Liners of MC-1 generators — 384
10.7.1	Commonly used metal liners — 384
10.7.2	Metal composite liners — 385
10.7.3	Shock-wave liners with phase transitions — 386
10.8	Violation of liner stability in flux compression — 390
10.9	Principle of cascading in MC generators of ultrahigh magnetic fields — 395
10.10	MC-1 cascade generator. Numerical simulation and experiment — 399
10.11	Ways of increasing the induction amplitude. Methods for control over the pulse shape. Capabilities of the MC-1 generator — 407
10.11.1	Methods for control over the shape and amplitude of an induction pulse — 407
10.11.2	Capabilities of MC-1 generators of ultrahigh magnetic fields — 410
10.12	Conclusion — 416
Supplement S10.	Calculation of the skin layer thickness and of the parameter q, characterizing the energy in the skin layer — 416
10.13	References — 418
Index	— 424