

Contents

Preface — v

List of contributing authors — xi

Mehmet Hakki Alma, Tufan Salan, Ayhan Tozluoglu, Oktay Gonultas, and Zeki Candan

1 Green composite materials from liquefied biomass — 1

- 1.1 Introduction — 1
- 1.2 Liquefaction technique — 2
- 1.3 Foams — 4
 - 1.3.1 Polyurethane foams (PUFs) from liquefied lignocellulosics — 5
 - 1.3.2 Phenolic foam from liquefied lignocellulosics — 8
- 1.4 Molding materials — 10
 - 1.4.1 Liquefied wood as replacement in novolac-type resin-based composites — 12
 - 1.4.2 Epoxy-type resins from liquefied biomass — 16
- 1.5 Fibers — 17
 - 1.5.1 Fibers from liquefied lignocellulosics — 19
 - 1.5.2 Carbon and activated-carbon fiber from liquefied lignocellulosics — 19
- 1.6 Films and coatings — 21
 - 1.6.1 Liquefaction of biomass for polyester production — 21
 - 1.6.2 Liquefied biomass as replacement for polyurethane films — 24
 - 1.6.3 Self-crosslinking film from liquefied biomass — 24
- 1.7 Liquefied wood as replacement in fiber and ceramic — 24
- 1.8 Conclusion — 27

Prasanta Sahoo, Suman Kalyan Das, and Samir Kumar Acharya

2 Tribological aspects of natural fiber composites — 33

- 2.1 Introduction — 33
- 2.2 Significance of tribology in development of materials — 34
- 2.3 Natural fiber composites — 34
 - 2.3.1 About natural fibers — 35
 - 2.3.2 Classification of natural fibers — 35
 - 2.3.3 Classification of green composites — 37
 - 2.3.4 Applications of natural fiber composites — 40
- 2.4 Chemical modification of fiber surface-improving fiber-matrix adhesion — 41
 - 2.4.1 Alkaline treatment — 42
 - 2.4.2 Benzoyl chloride treatment — 43
 - 2.4.3 Permanganate treatment — 43

2.5	Mechanical characteristics of natural fiber composites —	44
2.5.1	Effect of micro- and nanofiller —	46
2.5.2	Morphology of tensile tested composites —	49
2.6	Tribological behavior of natural fiber composites —	50
2.6.1	Measuring friction and wear —	51
2.6.2	Friction characteristics of natural fiber composites —	52
2.6.3	Wear behavior of natural fiber composites —	53
2.6.4	Post-test morphology and wear mechanism —	59
2.6.5	Tribological anisotropy in natural fiber composites —	61
2.7	Closure —	64

S. Manoharan, V. Krishnaraj, R. Vijay, D. Lenin Singaravelu, and B. Suresha

3	Development and characterization of novel fiber reinforced hybrid friction composites —	69
3.1	Introduction —	69
3.1.1	Research gap based on literature inference —	71
3.1.2	Objectives of the present study —	71
3.2	Materials and method —	72
3.2.1	Materials —	72
3.2.2	Processing —	75
3.2.3	Experimentation —	76
3.3	Results and discussion —	82
3.3.1	Thermal, mechanical and thermomechanical analysis of basalt-recycled aramid fiber reinforced friction composites —	82
3.3.2	Abrasive wear behavior of basalt-recycled aramid fiber reinforced hybrid friction composites —	87
3.3.3	Fade and recovery behavior of basalt-recycled aramid fiber reinforced friction composites —	102
3.4	Conclusion —	111

J. Babu, Jose Philip, and J. Paulo Davim

4	Machining defects in green composites —	115
4.1	Introduction —	116
4.2	Defects in drilling of NFRCs —	116
4.2.1	Delamination in NFRCs —	118
4.2.2	Mechanisms of delamination —	118
4.2.3	Methods of measuring delamination —	119
4.2.4	Assessment of delamination —	119
4.2.5	Delamination in NFRCs —	122
4.2.6	Geometrical errors —	123
4.2.7	Thermal damages —	123

4.3	Machining defects in milling —	124
4.3.1	Delamination in milling —	125
4.3.2	Geometrical errors —	126
4.4	Machining defects in turning —	128
4.5	Summary —	128

M. A. A. Aldahdooh, Ali Alnuaimi, A. Jamrah, N. Muhamad Bunnori,
M. A. Megat Johari, and M. I. Martini

5	GUSMRC – From concept to structural application —	133
5.1	Introduction —	133
5.2	UHPFRCCs: Definition and constituent materials —	133
5.3	POFA: definition and its applications in concrete production —	135
5.3.1	UPOFA treatment procedure —	136
5.4	GUSMRC definition, development, and its applications —	137
5.4.1	Development process —	137
5.4.2	Tensile behavior of GUSMRC —	139
5.4.3	GUSMRC application —	140
5.5	Conclusion —	142
5.6	Recommendations for future research —	142

Index — 147