

Contents

1	Introduction to plug-and-play control	1
1.1	Plug-and-play control	1
1.2	Motivation and application scenarios	2
1.2.1	Motivation example: Power networks	2
1.2.2	Application scenarios used in this thesis	4
1.2.3	Further application scenarios	5
1.3	Problem formulation and fundamental questions	6
1.3.1	The plug-and-play control problem	6
1.3.2	Approaches and fundamental questions	8
1.4	Literature on plug-and-play control	10
1.4.1	Controller design with limited model information	10
1.4.2	Plug-and-play in networked control systems	14
1.4.3	Plug-and-play in manufacturing systems	15
1.4.4	Implementation of plug-and-play control	16
1.4.5	Classification of this thesis	16
1.5	Contributions of this thesis	17
1.6	Structure of this thesis	19
2	Preliminaries	23
2.1	Notation and definitions	23
2.1.1	General notation	23
2.1.2	Definitions on stability	25
2.1.3	Convex sets	26
2.1.4	Linear matrix inequalities	29
2.1.5	Set invariance in control	30
2.1.6	Graph theory	31
2.2	Models	31
2.2.1	Interconnected system	31
2.2.2	Controlled interconnected system	34
2.2.3	Communication network	34

2.3	Robust control techniques	34
2.3.1	Systems with unknown-but-bounded model uncertainty	35
2.3.2	Basics on H_∞ -norm	37
2.4	Fault-tolerant control methods	39
2.4.1	Model of the faulty subsystem	39
2.4.2	Controller reconfiguration by a virtual actuator	40
2.4.3	Model-based fault diagnosis	41
2.5	Demonstration examples	44
2.5.1	Interconnected thermofluid process	45
2.5.2	Multizone furnace	47
3	Handling of model information	49
3.1	Connection of models	49
3.2	Models of plug-and-play control	53
3.2.1	Global view and local view	53
3.2.2	Models from the local view	54
3.3	Design agents	58
3.4	Interconnection graph and communication graph	59
3.4.1	Interconnection graph	59
3.4.2	Communication graph	60
4	Plug-and-play control using the model of the physical interaction	63
4.1	Problem formulation	63
4.2	A distributed algorithm to model the physical interaction	65
4.3	Analysis of the modelling algorithm	69
4.4	Application scenario: Fault-tolerant control	74
4.4.1	Local reconfiguration with a virtual actuator using the model of the physical interaction	74
4.4.2	Plug-and-play reconfiguration algorithm	76
4.4.3	Example: Interconnected tank system	77
5	Plug-and-play control using the local model based on restricted operating sets	81
5.1	Problem formulation	81
5.2	Conditions to enable the design with the local model	83
5.3	Local design conditions	87
5.3.1	Boundedness conditions	87
5.3.2	Performance conditions	88

5.4	Controller design based on robustly positively invariant operating sets	90
5.4.1	LMI-based design of a static state-feedback	90
5.4.2	Design of a tube-based model predictive controller	93
5.5	Application scenario: Fault-tolerant control	102
5.5.1	Plug-and-play reconfiguration algorithm	103
5.5.2	Experiment: Interconnected thermofluid process	104
5.5.3	Further application scenarios	111
6	Plug-and-play control using the local model based on limited amplifica-	113
	tions	
6.1	Problem formulation	113
6.2	Conditions to enable the design with the local model	115
6.3	Local design conditions	119
6.3.1	I/O stability conditions	119
6.3.2	I/O performance conditions	124
6.4	H_∞ -controller design	127
6.5	Application scenario: Integration of new subsystems	133
6.5.1	Plug-and-play integration algorithm	133
6.5.2	Experiment: Interconnected thermofluid process	136
6.5.3	Further application scenarios	142
7	Plug-and-play control using an approximate model of the physical inter-	143
	action	
7.1	Problem formulation	143
7.2	A local algorithm to approximate the dynamics of the physical interaction . . .	146
7.2.1	Separation of relevant and irrelevant dynamics	146
7.2.2	A measure of the coupling strength	149
7.2.3	A local condition to adjust the accuracy of the interaction model	151
7.2.4	Model procurement algorithm	158
7.3	Cooperative design conditions	160
7.3.1	Conditions to enable the design with an approximate model of the phys-	
	ical interaction	160
7.3.2	I/O stability conditions	164
7.3.3	I/O performance conditions	168
7.3.4	H_∞ -controller design	170

7.4	Application scenario: Fault-tolerant control	171
7.4.1	Local reconfiguration with a virtual actuator using an approximate model of the physical interaction	172
7.4.2	Plug-and-play reconfiguration algorithm	174
7.4.3	Example: Multizone furnace	174
7.4.4	Further application scenarios	179
8	Plug-and-play diagnosis using an approximate model of the physical interaction	181
8.1	Problem formulation	181
8.2	Models of plug-and-play diagnosis	184
8.2.1	Approximate model for the design of the diagnosis system	184
8.2.2	Structure of the local diagnosis system	187
8.3	Design of the residual evaluation	188
8.3.1	Design issues	188
8.3.2	Tolerance bands of the residuals	189
8.3.3	Robust fault detectability and robust fault isolability	192
8.3.4	Thresholds for fault detection and fault isolation	194
8.4	Design of the residual generation	196
8.4.1	Design issues	196
8.4.2	A robust residual generator	196
8.5	Plug-and-play diagnosis algorithm	203
8.6	Example: Multizone furnace	206
9	Conclusion	211
9.1	Summary	211
9.2	Outlook	213
	Bibliography	215
	Appendices	231
A	Models of the demonstration processes	233
A.1	Interconnected thermofluid process model	233
A.1.1	Nonlinear model	233
A.1.2	Linearised model	235
A.2	Multizone furnace	237

B Proofs	239
B.1 Proof of Theorem 4.1	239
B.2 Proof of Corollary 4.1	240
B.3 Proof of Theorem 5.1	241
B.4 Proof of Corollary 5.1	242
B.5 Proof of Corollary 5.2	242
B.6 Proof of Lemma 6.1	243
B.7 Proof of Theorem 6.3	244
B.8 Proof of Lemma 7.1	246
B.9 Proof of Theorem 7.2	247
B.10 Proof of Lemma 7.2	248
B.11 Proof of Theorem 7.3	249
B.12 Proof of Proposition 7.2	251
B.13 Proof of Corollary 7.5	252
C Construction rules of transfer functions	255
C.1 Physical interaction, relevant part and irrelevant part	255
C.2 Cooperatively controlled subsystem	257
D List of symbols	259