

Contents

1	Introduction	1
1.1	Point-of-care testing	1
1.2	Asymmetric nanofluidic grating detector	5
1.3	Outline	5
2	Fundamentals	7
2.1	Optofluidic refractive index measurements	8
2.2	Immunoassay - surface modification for biosensing	14
2.3	Point-of-care diagnostics	17
2.3.1	Smartphone-based POC devices	18
2.3.2	Rapid prototyping for POC readout devices by 3D printing	19
2.3.3	POC diagnostics for Buruli ulcer	20
2.4	Micro-fabrication technologies	20
2.5	Theoretical background	25
2.5.1	Diffraction of light	25
2.5.2	Transport and surface related reaction conditions in microfluidic systems	32
3	Asymmetric optical grating	39
3.1	Concept	40
3.2	Mathematical model	42
3.3	Findings of the mathematical model	44
3.3.1	Common mode rejection	45
3.3.2	Impact of asymmetry	48
3.3.3	Impact of channel depth	49
3.3.4	Impact of the channel wall phaseshift	50
3.3.5	Other considerations	52
4	Fabrication and experimental setup	59
4.1	Prerequisites	60

4.2	Fabrication process	60
4.2.1	SOI-based chip fabrication	60
4.2.2	Alternative fabrication for cost and time reduction . . .	61
4.3	Fluidic interface and control	65
4.4	Optical setup for chip readout	67
5	Proof-of-principle	69
5.1	Required limit of detection - first estimation	70
5.2	Detection of refractive index differences	70
5.2.1	Materials and methods	71
5.2.2	Results	71
5.3	Common mode rejection	75
5.3.1	Materials and methods	75
5.3.2	Results	75
6	Label-free biosensing	79
6.1	Protein detection: Biotin-streptavidin binding	80
6.1.1	Materials and methods	80
6.1.2	Results	80
6.2	Detection of <i>Mycobacterium ulcerans</i> antigen MUL2232	83
6.2.1	Materials and methods	83
6.2.2	Results	85
6.3	Mass transport conditions and quantitation	87
6.3.1	Material and methods	87
6.3.2	Fluid velocity and mass transport conditions	87
6.3.3	Secondary antibody detection	89
6.4	Smartphone-based POC device	94
6.4.1	Mobile optical setup	95
6.4.2	Smartphone application	96
6.4.3	Materials and methods	97
6.4.4	Characterisation	98
6.4.5	Common mode rejection	99
6.4.6	Protein detection with the mobile setup	102
6.4.7	Perspective	102
7	Particle detection and quantitation	105
7.1	Motivation	106
7.2	Theoretical background and mathematical model	108

7.3	Polystyrene particles detection	114
7.3.1	Materials and methods	114
7.3.2	PIV measurements	116
7.3.3	Diffractive measurement of particle suspensions	119
7.3.4	Clogging of the nanochannels	123
7.3.5	Virus titer determination - an outlook	125
8	Conclusion and outlook	127
9	Bibliography	135
9.1	List of References	135
9.2	List of Own Publications	161
9.3	List of Student Theses	164
Appendix		165
A	Matlab code for mathematical model	166
B	Results of the mathematical model: Second mode	168
C	Quantisation noise - example	170
D	Process plan: Generation 1	171
E	Supply channel cross section for both fabrication protocols	178
F	Process plan: Generation 2	179
G	Improved alignment structures	183
H	Optical setup	184
I	Reflectivity at thin layers	185
J	Non-uniform protein distribution in the grating channels	186
K	Functionalisation with anti-mouse	187
L	Matlab script for suspension exchange model	188