

Contents

Danksagung	iii
Abstract	v
Zusammenfassung	vii
1 Introduction	1
2 Theoretical background	7
2.1 Introduction	9
2.2 Basics of microgels	9
2.3 Fabrication of spherical microgels	12
2.3.1 Emulsion polymerization	12
2.3.2 Precipitation polymerization	14
2.4 Fabrication of anisometric microgels	16
2.4.1 Microfluidics	17
2.4.2 Lithographic methods	18
2.5 Continuous reactors	20
2.5.1 Continuous stirred-tank reactors	20
2.5.2 Plug flow reactor	21
2.6 Optical principles for projection lithography	23
2.6.1 Basic image projection in projection lithography	23
2.6.2 Optical phenomena in image projection	24
2.6.3 Numerical aperture (NA)	26
2.6.4 Resolution and depth of focus	27
2.6.5 Köhler illumination	28
2.6.6 Influence of the light intensity	29
2.7 Conclusion and research potential	30
3 From batch to continuous precipitation polymerization	33
3.1 Introduction	35
3.2 Experimental section	36
3.2.1 Materials	36
3.2.2 Microgel synthesis in a batch reactor	36
3.2.3 Reaction calorimetry in batch synthesis	37
3.2.4 Microgel synthesis in a flow reactor	37

3.2.5	Dynamic light scattering	39
3.2.6	Static light scattering	40
3.3	Results and discussion	41
3.3.1	Operation mode and calorimetry	41
3.3.2	Influencing factors on the microgel size	43
3.3.3	Temperature responsive behavior of spherical microgels	45
3.3.4	Comparison of the inner structure of the fabricated microgels	47
3.4	Conclusion	49
4	Soft temperature-responsive microgels of complex shape	51
4.1	Introduction	53
4.2	Experimental section	53
4.2.1	Materials	53
4.2.2	Customized setup	53
4.2.3	Preparation of reaction solution	56
4.2.4	Investigation of microgel stiffness	56
4.2.5	Investigation of temperature-responsive behavior	57
4.3	Results and discussion	58
4.3.1	Stop-flow lithography with NIPAm	58
4.3.2	Influence of polymerization parameters	60
4.3.3	Diffusion during polymerization	63
4.3.4	Stiffness of PNIPAm rods	64
4.3.5	The temperature-responsive behavior of PNIPAm snowflakes	66
4.4	Conclusion	69
5	Fabrication limits of SFL	73
5.1	Introduction	75
5.1.1	Theoretical influences and phenomena in SFL	75
5.1.2	Polymerization-parameter windows	77
5.1.3	Fluidic parameters	78
5.1.4	Mask pattern size and distance	79
5.2	Experimental	80
5.2.1	Materials	80
5.2.2	Preparation of reaction solutions	80
5.2.3	Setup and special setup adjustments	81
5.2.4	Investigations of polymerization-parameter windows	83
5.2.5	Investigation of fluidic parameters and the age of reaction solution	84
5.2.6	Investigation of the mask pattern size and distance	85

5.3	Results and discussion	87
5.3.1	Influence of the initiator type and amount on the polymerization parameters	87
5.3.2	Parameter windows using varying prepolymer amounts	89
5.3.3	Shape of PEGDA microgels for different polymerization parameter	90
5.3.4	Age of reaction solution	93
5.3.5	Pattern size and distance influence the sticking behavior at the upper polymerization limit	99
5.4	Conclusion	104
6	Variations in polymeric structure of anyshape microgels in SFL	109
6.1	Introduction	111
6.2	'Macro'porous microgels	111
6.2.1	Experimental	113
6.2.2	Results	115
6.3	Microgels with carbon nanotubes	122
6.3.1	Experimental	123
6.3.2	Results with carbon nanotubes	125
6.4	Microgels with maghemite nanospindels	126
6.4.1	Experimental	127
6.4.2	Results for microgels with maghemite nanospindels	129
6.5	Conclusion	132
7	Conclusions	135
	Bibliography	139
	Appendix	157
A.1	Supplementary to chapter 4	159
A.1.1	Fabrication of thin PNIPAm rods using SFL	159
A.1.2	In-flow behavior of thin PNIPAm rods containing 4 wt% BIS	161
A.1.3	Dynamic behavior of a PNIPAm snowflake during heating and cooling	161
A.2	Supplementary to chapter 5	165
A.2.1	Aging of the PEGDA reaction solution	165
A.3	Supplementary to chapter 6	167
A.3.1	First approximation of parameter windows for the NIPAm-methanol polymerization system	167
A.3.2	FESEM images from 'macro'porous microgels from NIPAm-methanol polymerization system	169