

Contents

Acknowledgments — VII

Disclaimer — IX

Preface — XI

Conversion factors — XIX

Physical constants — XXI

Nomenclature — XXIII

1 An overview of the equipment — 1

- 1.1 Process applicability — 2
 - 1.1.1 Types of hairpins — 3
 - 1.1.2 Primary concerns — 5
 - 1.1.3 Where to use a double-pipe exchanger? — 5
 - 1.1.4 About the optimal design — 7
- 1.2 The double-pipe exchanger is actually a hairpin! — 10
- 1.3 Pipes and tubes — 13
 - 1.3.1 Is there a difference? — 13
 - 1.3.2 Practical implications of pipe and tube distinction — 14
 - 1.3.3 Commercial diameters and lengths — 14

2 Heat exchanger design equations — 17

- 2.1 Heat load — 17
- 2.2 The design equation — 20
- 2.3 The overall heat transfer coefficient — 21
 - 2.3.1 “Design” and “clean” overall heat transfer coefficients — 24
 - 2.3.2 Relatively small wall thermal resistance — 25
 - 2.3.3 Controlling fluid — 25
- 2.4 Basic heat exchanger differential equations — 28
 - 2.4.1 Parallel flow — 29
 - 2.4.2 Counterflow — 31
- 2.5 Log mean temperature difference — 32
 - 2.5.1 Parallel flow double-pipe heat exchanger — 33
 - 2.5.2 Counterflow double-pipe heat exchanger — 35
 - 2.5.3 The restrictions on the overall heat transfer coefficient — 36
 - 2.5.4 LMTD and fluid flow arrangement — 37
 - 2.5.5 Special cases of LMTD — 39

2.5.6	The physical meaning of LMTD —	39
2.5.7	Do we need LMTD nowadays? —	39
2.5.8	Area sizing using the descriptive differential equations —	40
2.5.9	Parallel flow or counterflow: what is the difference? —	41
2.6	Exit temperatures of fluids —	43
2.6.1	Counterflow —	43
2.6.2	Parallel flow —	45
	Problems —	52
3	Wall temperatures —	57
3.1	Cold fluid in the inner pipe —	58
3.1.1	Negligible conductive resistance —	59
3.1.2	Thin tube wall —	59
3.2	Hot fluid in the inner pipe —	60
3.2.1	Negligible conductive resistance —	61
3.2.2	Thin tube wall —	61
3.3	General form of wall temperature equations —	61
3.3.1	Significant conductive and convective resistances —	61
3.3.2	Negligible conductive wall resistance —	62
3.3.3	Thin tube wall —	62
	Problems —	64
4	Heat transfer coefficients —	67
4.1	Methods of estimation —	67
4.1.1	Types of correlations —	68
4.2	Using correlations —	69
4.3	Flow regimes —	70
4.4	Effects of fluid flow development —	71
4.4.1	Fully developed laminar flow in pipes —	72
4.5	Heat transfer coefficients for circular pipes —	73
4.5.1	Laminar flow —	73
4.5.2	Turbulent flow —	77
4.5.3	Transition flow —	92
4.5.4	Heat transfer coefficients for water —	94
4.5.5	Liquid metals —	95
4.6	Heat transfer coefficients for the annulus —	100
4.6.1	Annulus equivalent diameter —	101
4.6.2	Petukhov–Roizen corrector —	101
4.6.3	Gnielinski annulus equation —	102
	Problems —	104

5 Pressure drop — 107

- 5.1 Friction factor in circular tubes — 108
 - 5.1.1 Isothermal laminar flow — 109
 - 5.1.2 Isothermal turbulent flow — 109
 - 5.1.3 All flow regimes — 110
 - 5.1.4 Effect of variable physical properties — 112
- 5.2 Pressure drop calculation with the 2- K method — 112
- 5.3 Inner tube pressure drop — 113
 - 5.3.1 Distributed pressure drop — 114
 - 5.3.2 Localized pressure drop — 114
- 5.4 Annulus pressure drop — 118
 - 5.4.1 Distributed pressure drop — 119
 - 5.4.2 Localized pressure drop — 119
 - 5.4.3 Annulus with bonnet-type return — 121
 - 5.4.4 Annulus with straight-pipe return — 123
- 5.5 Allowable pressure drop — 125
 - Problems — 127

6 Series-parallel arrangements — 131

- 6.1 Mean temperature difference — 133
 - 6.1.1 Hot fluid in series and cold fluid in parallel — 134
 - 6.1.2 Cold fluid in series and hot fluid in parallel — 135
 - 6.1.3 Choice of the fluid division — 136
- 6.2 Pressure drop calculation — 137
 - 6.2.1 Tube pressure drop — 137
 - 6.2.2 Annulus pressure drop — 137
 - Problems — 140

7 Heat exchanger design — 143

- 7.1 Fluid allocation — 143
- 7.2 Design margin — 144
 - 7.2.1 Over-design — 145
 - 7.2.2 Over-surface — 146
 - 7.2.3 Fouling over-surface — 146
 - 7.2.4 Design margin ranges — 146
- 7.3 Physical properties of chemical components — 147
- 7.4 Sizing — 148
 - 7.4.1 The design variables — 148
 - 7.4.2 Sizing outline — 149
- 7.5 Rating — 170
 - 7.5.1 Rating outline — 171

7.6	The data sheet — 172
	Problems — 192

8 Multi-tube heat exchangers — 195

8.1	Tube count — 195
8.2	Design method — 196
8.2.1	Cross-flow area — 196
8.2.2	Shell equivalent diameter — 196
	Problems — 204

9 Finned tube heat exchangers — 207

9.1	Fins count — 208
9.2	Design method — 209
9.2.1	Cross-flow area — 209
9.2.2	Shell equivalent diameter — 210
9.3	Fin efficiency — 210
9.4	Weighted fin efficiency — 210
9.5	Overall heat transfer coefficient — 211
9.6	Finned wall temperatures — 214
	Problems — 228

Appendix A Heat exchanger specifications — 233

A.1	Piping data (DN, NB, NPS) — 233
A.2	B.W.G.: Birmingham wire gauge — 239
A.3	Heat transfer tube data (B.W.G) — 241
A.4	Finned and multi-tube hairpin design data — 244

Appendix B Properties of materials — 249

B.1	Absolute roughness of materials — 249
B.2	Thermal conductivity of selected materials — 250

Appendix C Physical properties of chemical components — 253

C.1	Index — 253
C.2	Selected gases: part A — 258
C.3	Selected gases: part B — 262
C.4	Selected vapors: part A — 267
C.5	Selected vapors: part B — 272
C.6	Selected vapors: part C — 277
C.7	Selected vapors: part D — 283
C.8	Selected vapors: part E — 288
C.9	Selected liquids: part A — 293
C.10	Selected liquids: part B — 298

C.11	Selected liquids: part C —	303
C.12	Selected liquids: part D —	308
C.13	Selected liquids: part E —	313

References — 319

List of gases — 325

List of vapors — 327

List of liquids — 329

Keyword index — 331