# Contents

**Abstract —— V**

**Preface —— VII**

**About the author —— XIX**

**0 Preamble: Introduction —— 1**
Introduction to the Thermal-Stimulated Depolarization (TSD) and the Thermal-Windowing Deconvolution (TWD) characterization techniques —— **1**

Part I: **A Dual and Cross-Dual interpretation of interactive coupling of conformers applied to Thermal-Stimulated Depolarization (TSD) and Thermal-Windowing Deconvolution (TWD)**

**1 Principle of Thermal-Stimulated Depolarization & Thermal-Windowing Deconvolution —— 15**
I.1.1 The different types of polarization —— **15**
I.1.1.1 Deformation polarization —— **17**
I.1.1.2 Dipolar orientation polarization —— **18**
I.1.2 Thermal-Stimulated Polarization and Depolarization —— **19**
I.1.3 Model calculation of the thermal-windowing steps —— **20**
I.1.3.1 General polarization equation —— **21**
I.1.3.2 Polarization stage —— **22**
I.1.3.3 Equations of depolarization —— **23**
I.1.3.4 Expression of the thermally stimulated current of depolarization —— **24**
I.1.3.5 Single Debye relaxation —— **25**
I.1.3.6 Distributed Debye processes —— **25**
I.1.4 Computer simulation —— **26**
I.1.5 Influence of $\Delta H$ and $\tau_o$ on a Debye relaxation peak —— **29**
I.1.6 Debye curve-fits —— **33**
I.1.6.1 The Bucci–Fieschi–Guidi integral solution —— **34**
I.1.6.2 The Lacabanne (2/3) rule —— **35**
I.1.6.3 Simplex curve-fitting methods —— **41**
I.1.6.4 Curve-fitting methods based on peak half-width —— **42**

Bibliografische Informationen
http://d-nb.info/124959572X

digitalisiert durch DEUTSCHE NATIONAL BIBLIOTHEK

I.1.7 Deconvolution of thermally windowed peaks — 44
I.1.8 Properties of Debye peaks. Influence of peak shifting on $\tau_o$ and $\Delta H$ — 46
I.1.9 Influence of the thermal-windowing experimental parameters on the characteristics of the depolarization peak — 56
I.1.9.1 Polarization voltage — 56
I.1.9.2 Effect of polarization time $t_p$ — 58
I.1.9.3 Effect of the time of depolarization $t_d$ — 59
I.1.9.4 Effects of the polarization temperature $T_p$ and the window width — 61
I.1.10 Acknowledgment — 64

**2 Thermal-Windowing Deconvolution, relaxation map analysis, and compensation phenomena to determine the amorphous state of polymers — 65**
I.2.1 Introduction — 65
I.2.2 Arrhenius transform. Relaxation map. Thermal-Windowing Deconvolution — 66
I.2.3 Eyring transform. Thermokinetic functions — 69
I.2.4 Compensation phenomena. Degree of disorder — 72
I.2.5 Compensation search. Z-structure. Z-line — 73
I.2.6 Determination of $T_g$. Activation entropy and enthalpy at $T_g$ — 80
I.2.7 DOD number — 80
I.2.8 Duality at $T_g$ — 83
I.2.9 Compensation in the sub-EE plane — 85
I.2.10 Normalization of the $\Delta G - T$ curves. Discussion — 92
I.2.10.1 Expression of the entropy $\Delta S_p$ vs. $T_p$ — 94
I.2.10.2 Expression of the enthalpy $\Delta H_p$ vs. $T_p$ — 98
I.2.10.3 Expression of the free energy $\Delta G$ vs. $T_p$ — 99
I.2.10.4 Discussion — 99
I.2.10.5 Conclusion — 100
I.2.11 Characterization of the amorphous phase in semi-crystalline polymers by TWD spectroscopy — 101
I.2.11.1 PTMG 2035 — 101
I.2.11.2 Polyamide 12 — 111
I.2.11.3 Polypropylene (undrawn and drawn) — 120
I.2.11.3.1 Undrawn polypropylene — 120
I.2.11.3.2 Drawn polypropylene — 127
I.2.11.3.3 Comparison between undrawn and drawn polypropylene — 134
I.2.12 Conclusion — 137

**3 A Dual and Cross-Dual interpretation of interactive coupling of conformers applied to thermally activated polarization and depolarization of polymers — 141**

I.3.1 Challenging results to the conventional models of polymer physics. Introduction to a new approach to the physics of polymer interactions: the Dual-Phase and Cross-Dual-Phase models — **141**

I.3.2 The $T_{g,\rho}$ peak and the $T_{LL}$ transition — **146**

I.3.3 Application of compensations to characterize interactive coupling in the amorphous state — **148**

I.3.3.1 Compensation laws — **148**

I.3.3.2 Compensations of $\Delta H$ and Ln $\tau_o$. Positive and negative compensations; the organization of the compensations in a super-compensation network. The Dual-Split model explanation — **149**

I.3.3.3 Effect of the voltage field on the statistics of interactive coupling. The nature of what TWD is actually deconvoluting — **164**

I.3.4 Normalization of the compensations between Ln($\tau_o$) and $\Delta H$. Introduction to "grid-shifting": a collateral shifting effect due to the interaction between the voltage field, temperature, and dielectric material — **167**

I.3.4.1 Geometrical and thermokinetic features of a Debye peak — **169**

I.3.4.2 Shifting the Debye peak obtained at a given $T_p$ by various amounts $\delta_x$ — **179**

I.3.4.3 Shifting the Debye peaks obtained at various $T_p$ by the same amount $\delta_x$: the three temperature ranges of the voltage field–temperature interactions — **181**

I.3.4.4 Shifting the Debye peak obtained at a given $T_p$ to a given temperature — **190**

I.3.4.5 Definition and description of "grid-shifting" — **204**

I.3.4.6 Grid-shifting unifies the correlations between Ln($\tau_o$) and $\Delta H$ across ranges 1, 2, and 3 into a mastercurve: on the determination of the framework relating relaxation time and temperature — **211**

I.3.4.6.1 Properties of the GRID — **211**

I.3.4.6.2 Description of the grid shift factors — **218**

I.3.4.6.3 The cross-dynamic structure of $T_p$: $T_p + \delta_{pH}$ and $T_p + \delta_{p\tau}$ — **223**

I.3.5 Discussion and conclusions — **233**

I.3.5.1 A survey of Chapter 3 developments — **233**

I.3.5.2 Interpretation of the TWD results by the Dual-Phase model of polymer interactions — **236**

I.3.5.2.1 The three ranges description of the amorphous state of polymers — **236**

I.3.5.2.2 Conclusions regarding the physical meaning of the results of TWD — **241**

I.3.5.3 General conclusions — **243**
I.3.5.4 The search for new concepts to build up a ladder of scales — **247**
I.3.5.4.1 The phantom variable $T_x$ — **247**
I.3.5.4.2 Conjugated states: $[\Delta H_c = \Delta H(T_p + \delta_{p\tau}), \tau_{oc} = \tau_o (T_p + \delta_{pH})]$ — **248**
I.3.5.4.3 The role of $T$, coupled to other independent external parameters, in the formulation of the interactions — **248**
I.3.5.4.4 Is this the way to end a serious book? — **249**

**Appendix of Part I — 251**
Conventional kinetics — **251**
Dual-Split Kinetics — **253**
Part A. Dual-Phase Dissipative Kinetics (vertical splitting) — **253**
A.1 Structuring between the *b* and *F* conformers — **253**
A.2 Vertical Dual-Split Kinetics — **254**
A.3 Examples of simulation of the vertical Dual-Split Kinetics equations (5) to (7) — **255**
A.3.1 Cooling simulation — **255**
A.3.2 Effect of cooling rate on the dynamics — **260**
A.3.3 Heating at constant rate — **261**
A.3.4 Isothermal return to equilibrium (annealing) — **263**
Part B. Horizontal splitting of $B_o$: creation of $N_s(t)$ energetic kinetic systems — **267**
B.1 Computer simulations — **268**
B.1.1 Cooling — **268**
B.1.2 Heating — **271**
B.1.3 Isothermal annealing — **272**
B.1.4 Influence of the initial number of systems $N_{so}$ — **275**
Part C. Compensating vertical and horizontal split constraints — **281**
Final word — **286**

**Part II: Application of Thermal-Stimulated Depolarization and Thermal-Windowing Deconvolution (TSD/TWD) to the characterization of the amorphous phase in polymers: case studies**

**1 A comparison of TSD/TWD, DSC, DEA, and DMA for the characterization of the amorphous phase of polymers — 289**
II.1.1 General description — **289**
II.1.2 Outputs. Resolution. Accuracy. Limitations — **297**
II.1.2.1 DSC — **297**
II.1.2.2 DMA and DEA — **302**

II.1.2.2.1 General considerations — 302
II.1.2.2.2 DMA — 305
II.1.2.2.3 DMA for coatings and adhesives: severe limitations — 307
II.1.2.2.4 DMA accuracy — 307
II.1.2.2.5 DEA — 308
II.1.2.2.6 Conclusion (DMA and DEA) — 309
II.1.2.3 TSD/TWD — 309
II.1.2.3.1 General considerations — 309
II.1.2.3.2 TWD accuracy — 317
II.1.2.3.3 Result of changing the baseline of integration — 317
II.1.2.3.4 Compensation search. Accuracy to determine the DOD number — 321
II.1.2.3.5 Isothermal depolarization experiments — 322
II.1.2.3.6 Spontaneous depolarization current — 324
II.1.2.3.7 The thermal-stimulated polarization current — 326
II.1.3 Conclusion — 327

**2 Practical examples of TSD characterization — 329**
II.2.1 Introduction: the nature of the peaks — 329
II.2.2 Selective polarization — 331
II.2.3 The $T_{g,p}$ peak and the measurement of "free volume" — 332
II.2.4 Coatings, paints, pigments, and pressure-sensitive adhesives on substrates — 340
II.2.4.1 Coatings — 340
II.2.4.1.1 Beverage container coatings — 341
II.2.4.1.2 Sanitary can coatings — 341
II.2.4.1.3 Powder coatings — 343
II.2.4.1.4 Plastic coatings — 344
II.2.4.2 Paints — 345
II.2.4.2.1 Case study: curing of polyester paint — 345
II.2.4.2.2 Case study: pre-painted coil coating quality control — 347
II.2.4.3 Pigments — 348
II.2.4.4 Pressure-sensitive adhesive on substrates — 350
II.2.5 Characterization of polyolefins — 351
II.2.5.1 TSD trace of polypropylene homopolymer — 352
II.2.5.2 TSD trace of atactic polypropylene — 352
II.2.5.3 Effect of orientation — 353
II.2.5.4 Polyethylenes of varying densities — 354
II.2.5.5 Effect of additives: Irganox 1076 — 355
II.2.5.6 Copolymers and blends (PE, HDPE, and EPR). TPOs — 356
II.2.5.7 Conclusions — 357
II.2.6 TSD in quality control applications — 358
II.2.6.1 Case study: TSD of "good" and "bad" LDPE tubes — 358

II.2.6.2 Case study: quality control in diaper fabrication — **359**
II.2.7 Nucleation effect sensed by space charges — **360**
II.2.8 Monofilaments and single strands — **362**
II.2.9 Wood and liquid crystal polymer — **363**
II.2.9.1 Case study: wood — **363**
II.2.9.2 Case study: relaxation in a liquid crystal polymer: Vectra 900 — **365**
II.2.10 Characterization of rubbers and elastomers — **373**
II.2.10.1 Case study: vulcanized blends of crosslinked elastomers — **373**
II.2.10.2 Case study: NR and SBR blends — **377**
II.2.11 Conclusion — **379**

**3 Practical examples of Thermal-Windowing Deconvolution characterization — 381**
II.3.1 Internal stress and the effect of the cooling rate on the DOD of engineering thermoplastics — **381**
II.3.2 Orientation and pressure effects on plastic materials — **383**
II.3.3 The curing of paint and powder coating on metal — **384**
II.3.3.1 Paints — **384**
II.3.3.2 Determination of DOD — **387**
II.3.3.3 Powder coatings — **389**
II.3.4 Structure of block copolymers and blends: how to quantify the level of interpenetration and segregation by thermal-windowing — **391**
II.3.4.1 Case study: characterization of latex copolymers by TWD — **391**
II.3.4.1.1 DSC — **391**
II.3.4.1.2 DMA — **392**
II.3.4.1.3 TSD — **392**
II.3.4.1.4 TWD — **392**
II.3.4.2 Case study: characterization of the structure of polyether block amide resins by TWD — **394**
II.3.4.3 Characterization of vulcanized rubber blends and crosslinked natural rubbers — **403**
II.3.4.3.1 Case study: characterization of vulcanized blend of NR and NBR — **404**
II.3.4.3.2 Case study: crosslinked natural rubber vulcanizates — **408**
II.3.4.3.3 Case study: characterization of NR/SBR blends of different concentrations — **408**
II.3.4.4 Case study: influence of LDPE blend on the relaxation map of HDPE — **422**
II.3.5 Case study: characterization by TWD of the effect of plasticizer concentration on the amorphous state of PMMA — **433**
II.3.6 Case study: characterization of the adhesive strength of pressure-sensitive adhesives by TWD — **446**

II.3.7 Case study: characterization by TWD of the influence of the $TiO_2$ content on the amorphous state of polystyrene — **450**
II.3.7.1 Discussion — **456**
II.3.8 Case study: influence of physical aging on the DOD and other thermokinetic parameters studied by TWD — **458**
II.3.8.1 Experimental procedure — **459**
II.3.8.2 Results — **460**
II.3.8.3 Discussion — **467**
II.3.8.4 Conclusion — **469**
II.3.9 Case study: characterization of PEEK and PEI/PEEK blends by TWD — **470**
II.3.9.1 PEEK — **470**
II.3.9.2 PEEK/PEI blend — **478**
II.3.10 Chapter conclusion — **483**

**4 Multiple compensation phenomena in the amorphous phase of polymers — 485**
II.4.1 Multi-compensations in a multi-phase system — **485**
II.4.2 Multiple compensation phenomenon in amorphous polystyrene and polycarbonate — **487**
II.4.2.1 Polystyrene — **487**
II.4.2.2 Polycarbonate — **502**
II.4.2.3 Conclusion — **504**
II.4.3 Multiple compensations in a polymer liquid crystal: Vectra — **504**
II.4.3.1 Discussion — **518**
II.4.4 Multi-compensations in wood samples — **521**
II.4.5 PEBA block copolymers revisited: a multi-compensations approach — **529**
II.4.6 Discussion and conclusion — **535**

**Book conclusions — 537**

**Bibliography — 553**

**Further reading — 565**

**Book acknowledgments — 577**

**Index — 579**