

Contents

List of Figures	IX
List of Tables	XIII
Notation	XV
Kurzfassung	XXI
Abstract	XXIII

1 Introduction	1
1.1 Future challenges	1
1.2 Copper: a key material	3
1.3 Structure of this thesis	5
2 State-of-the-art in decarbonization of copper production	7
2.1 Demand side management	8
2.1.1 Demand response potential in copper production	9
2.1.2 Demand response via process scheduling	10
2.1.3 Scheduling models in copper production	15
2.2 Industrial decarbonization by H ₂	16
2.2.1 Hard-to-abate greenhouse gas emissions	16
2.2.2 H ₂ supply and Power-to-H ₂ systems	18
2.2.3 Power-to-H ₂ systems	19
2.3 Contribution of this thesis	22
3 Demand response potential in copper production: Load shedding and load shifting	27
3.1 Copper production process	27
3.2 Methods and data	29
3.2.1 Load shifting algorithm	30
3.2.2 Load shedding costs	33
3.3 Results	34
3.3.1 Load shifting	34
3.3.2 Load shedding	35

3.4	Summary and conclusion	36
4	Demand response potential in copper production: a scheduling approach	37
4.1	Copper production	38
4.2	Scheduling model description	40
4.2.1	Resource-Task Network and copper scheduling models	40
4.2.2	Problem description	41
4.2.3	Parameters and data	44
4.2.4	Solution procedure	46
4.3	Results	47
4.3.1	Influence of scheduling horizon	48
4.3.2	Cost-optimal schedules	49
4.3.3	Sensitivity analysis	54
4.3.4	Discussion	57
4.4	Conclusions	58
5	Decarbonizing copper production by Power-to-Hydrogen	61
5.1	Material and data: Retrofitting copper production with Power-to-H ₂ . .	62
5.1.1	Conventional copper production	62
5.1.2	Copper production with Power-to-H ₂ and -O ₂	63
5.1.3	Power-to-H ₂ system	68
5.1.4	Indirect GHG emissions	72
5.1.5	Commodity prices and time of energy use	72
5.2	Method and problem description	75
5.2.1	Optimization formulation	76
5.2.2	Successive decarbonization	80
5.3	Results and discussion	80
5.3.1	Decarbonizing copper production	81
5.3.2	Total GHG emissions	87
5.3.3	Future technology developments	90
5.3.4	Discussion and implications	96
5.4	Conclusions	97
6	Demand response potential of the decarbonized copper production	99
6.1	Process scheduling model with Power-to-H ₂	99
6.1.1	Power-to-H ₂ systems: scheduling and demand response	99
6.1.2	Scheduling model extension by Power-to-H ₂	100
6.2	Optimal DR scheduling of the decarbonized process	107
6.2.1	CO ₂ abatement cost of the scheduled decarbonized system . . .	107

6.2.2	Electricity costs and shifted electricity demand	110
6.2.3	Future electricity prices & residual load shares	114
6.2.4	Sensitivity of Power-to-H ₂ system sizing	117
6.3	Conclusions	120
7	Summary, conclusions, and outlook	123
7.1	Summary and conclusions	123
7.2	Outlook & future perspectives	126

Appendices

A	Revenue streams of copper production	133
B	Scheduling model parameters of conventional process	135
C	Further impacts of water electrolyzer development on decarbonization	143
C.1	Impact on the cost per product	143
C.2	Impact on the Power-to-H ₂ system design	145
D	Parameters and additional results of decarbonized scheduling model	149
D.1	Model extension and additional parameters	149
D.2	Additional results for scheduling decarbonized copper production . . .	151
D.2.1	Optimal DR scheduling of decarbonized copper production . . .	152
D.2.2	Electricity demands in 2050 Power-to-H ₂ designs	154
D.2.3	Detailed costs of the decarbonized copper production designs . .	155
D.2.4	Annual electricity costs with electricity prices in 2030	157
E	Publications and student theses	161
	Bibliography	163