

Table of Contents

1	Introduction	5
2	Injection Technology	6
2.1	The Injection Molding Cycle	7
3	Useful Equations and Theory	14
4	Examples	24
4.1	Runner System Balance	24
4.2	Shrinkage Prediction	25
4.3	Cooling Time Prediction	27
4.4	Effect of Process Parameters on Shrinkage	28
4.5	Theoretical Energy Consumption in an Injection Molding Process with PS	29
4.6	Processing Conditions of PA6 Parts and Theoretical Power-Cooling Requirement	30
4.7	Theoretical Water Flow Requirement for a Mold for PA6 Parts	34
4.8	Determining Viscosity Constants from the Curve	35
5	Polymer Data (for Standard Materials without Fillers or Modifiers)	37
5.1	Polyolefins	37
5.1.1	Low Density Polyethylene (LDPE)	37
5.1.2	High Density Polyethylene (HDPE)	41
5.1.3	Polypropylene Homopolymer (PP)	45

5.2	Styrenics	49
5.2.1	Polystyrene Homopolymer (PS)	49
5.2.2	High Impact Polystyrene (HIPS)	53
5.2.3	Styrene/Acrylonitrile Copolymer (SAN)	57
5.2.4	Acrylonitrile/Butadiene/Styrene Copolymer (ABS)	61
5.3	Polycondensates	65
5.3.1	Polyamide 6 (PA6)	65
5.3.2	Polyamide 66 (PA66)	69
5.3.3	Polyethylene Terephthalate (PET)	73
5.3.4	Polybutylene Terephthalate (PBT)	77
5.3.5	Polycarbonate (PC)	81
5.3.6	Polyphenylene Ether Modified (m-PPE)	85
5.3.7	Polyether Etherketone (PEEK)	89
5.3.8	Polyarylsulfone (PSU)	93
5.4	Vinyls	97
5.4.1	Polyvinylchloride (PVC) Rigid	97
5.4.2	Polyvinylchloride (PVC) Flexible	101
5.5	Others	105
5.5.1	Polylactic Acid (PLA)	105
5.5.2	Polymethylmethacrylate (PMMA)	109
5.5.3	Polyacetal (POM)	113
6	Appendix	117
7	Definitions	120
8	Further Reading	123