

Index

a

ABCD matrix 190
 Abel transform 69
 Abel inversion 92
 absorption coefficient 130–132
 active diagnostics 65–115, *See also*
 Polarimetry; Reflectometry; Scattering;
 Interferometry
 Airy function 89
 all-digital phase measurement 301–303
 all-digital phase meter 301, 302
 Altar–Appleton–Hartree-equation 31, 41,
 147
 alternative decorrelation 271–272
 – single-sightline correlation experiments
 272
 analog output, phase measurements with
 299–300
 antenna arrays
 – array factor 219
 – element factor 219
 antennas 208–221
 – antenna arrays 217–221
 – – frequency-scanned array 220
 – – phased array 218
 – antenna gain 209
 – antenna temperature 211–212
 – antenna theorem 210, 258
 – basic definitions 208–211
 – characterizing parameters 209
 – conical horn 214–215
 – directivity 210
 – Gaussian beam excitation 217–219
 – pyramidal horn 212–213
 – receiving 208
 – transmitting 208
 anti-Hermitian part of dielectric
 tensor 23

antireflection coating 198
 aspect ratio 5

b

B_0 -field varying along sightline 135–137
 backward waves 219
 backward-wave oscillator (BWO) 203–205,
 334
 band-pass filter 292
 – general definitions 293–294
 – metallic meshes 298–300
 – in overmoded waveguide 295–297
 bandwidth influence on sensitivity 259–260
 beam radius 56
 beam waist 56
 Bessel functions 172, 174
 bistatic arrangement 334
 bi-refrindexence
 – circular 38
 – linear 39
 bolometer 223–225
 – composite bolometer 223
 – hot electron bolometer 225–226
 Boltzmann equation 25
 Bragg-back-scattering 99
 break-even condition 9
 bremsstrahlung 117–122
 Brillouin angle 178
 Budden parameter 146
 burning plasma experiment (BPX) 375

c

cascaded systems, noise temperature of
 250–251
 chain parameters 281
 characteristic impedance 152–153
 characteristic impedance of free space
 162

circular waveguides 170–176
 – fields in 171
 – loss in 175–176
 circulator 287
 coaxial transmission line 161–163
 – characteristic properties 162
 – losses in 162–163
 coherent detectors 221, 237
 coherent Thomson-scattering (CTS) 106,
 108–109, 373–375
 cold-plasma dispersion relations 34–42
 – finite-temperature correction to 42–48
 – nonmagnetized plasma 34
 cold-plasma limit 29–32, 390
 collision frequency 33
 components and subsystems 275–313,
 See also Network-analysis measuring
 techniques
 composite bolometer 223
 Compton effect 105
 confocal parameters 188
 conical horn 214–215
 constant fraction discriminator 342
 control loop components 308–309
 correlation radiometry 264–272
 – cross-correlation function 265–267
 – intensity fluctuations 264–266
 – – and coherence 266–267
 corrugated circular waveguides 182–185
 – fields of 183–185
 corrugated waveguide 182–183
 Cotton–Mouton polarimeter 75, 327,
 330–322
 – common generalized description 77–83
 Cotton–Mouton effect 75, 326–327
 coupling coefficient for fundamental
 Gaussian beams 194–196
 cross correlation 267
 – accuracy of measurements 270–271
 – function 267–268
 crossed-waveguide construction 233
 curvature parameter 234
 curved mirrors 191–193
 cyclotron emission imaging (ECEI) 347
 cyclotron harmonic waves 145

d

1 dB compression point 305
 Debye length 20
 degenerate mode 174
 density fluctuations
 – influence, in reflectometry 95–100
 – role 108
 density gradient length 87

deuterium 3
 detection 221–236, *See also* Bolometer;
 Diode direct detector; Heterodyne detection
 – coherent detectors 221
 – incoherent detectors 221
 – noise-equivalent power (NEP) 226
 – optimization 221–222
 – – linearity 224
 – – noise level 221
 – – sensitivity 221
 – – stability 224
 – – temporal resolution 224
 – – voltage or current responsivity 221
 – Schottky diode 227–229
 deuterium–tritium (DT) fusion reaction 3
 device under test (DUT) 288
 dielectric tensor from kinetic theory 25
 digital prescalars 310
 digital-to-analog convertor (DAC) 301–302
 diode direct detector 231–233
 diode mixer 239–241
 directional coupler 281–283
 directivity 210
 dispersion interferometer 323
 dispersion relation of the mode 22
 Doppler broadening 140
 Doppler reflectometry 346–348
 Doppler shift 102–103
 dot matrix Schottky diode 230
 down-shifted frequency 123
 DT reaction 2
 dynamic range of a component 304

e

Echelette grating 356
 effective ion charge 119
 eigenmodes 165
 eikonal phase 49
 electron Bernstein wave emission 143–149
 – detection 370–373
 – electron Bernstein waves 144–146
 – mode conversion 146–149
 – O–X–B mode conversion 143
 electron cyclotron emission (ECE), radiometry
 of 349–370
 – calibration 370
 – general requirements 350–354
 – heterodyne radiometers 357–362
 – imaging (ECEI) 362–363
 – system parameters 363–366
 electron cyclotron emission (ECE) 122–143
 – absorption coefficient 130–132
 – B_0 -field varying along sightline 135–137

- electric field and spectrum, single electron 123–126
- electron cyclotron absorption (ECA) measurement 142–143
- electron motion in a static field 122–123
- emission profile 132–135
- optical depth of most relevant modes 137–140
- perpendicular observation, characteristic modes 126–128
- spectrum, electron ensemble 128–130
- visibility depth and localization 140–142
- electron cyclotron frequency 27
- electron cyclotron resonance heating (ECHR) 10, 290
- electron gyration radius 122
- electron motion in a static field 122–123
- elliptical waveguide 373
- emission profile 132–135
- emissivity 128
- energy confinement time 8
- even Matthieu functions 373
- extraordinary mode (X-mode) 39

f

- Faraday effect 71–75, 82
- Faraday polarimeter 329–330
- far-infrared (FIR) wavelength 319
- fast X-wave 146
- finite Larmor radius (FLR) approximation 42–44
- finite-size probing beam 54–58
- finite-temperature correction to cold-plasma dielectric tensor 42–48
- first-order active loop filter 311
- first-order product 307
- fluctuation measurements 345–346
- flux surface 4
- form factor 104
- Fourier–Bessel expansion 124, 244
- Fourier spectroscopy 352
 - Fellgett advantage 355
 - Jaquinot advantage 355
- free–free radiation 117
- frequency-selective filters 290–299
 - band-pass filter 290
 - high-pass filter 290
 - low-pass filter 290
- frequency stability 308–312
 - control loop components 308–309
 - first-order active loop filter 311
 - phase margin 312
 - theoretical concept 310–312
- frequency-scanned antenna array 220

- frequency-selective surfaces (FSS) 299
- fringes 299
- full width at half maximum (FWHM) 90, 93, 341
- fundamental dispersion relation of waves in plasmas 22
- fundamental mode 57
- fundamental TE₁₀-wave 167–170
- fusion research 1–17
 - magnetic plasma confinement 4–10
 - proton-proton-chain (pp-chain) 2
 - reaction scheme 1–3

g

- gain compression 304–305
- Gauss-Hermite polynomials 57
- Gaussian beam 185–196
 - coupling coefficient for 194–196
 - description 55–58
 - excitation of 215–217
 - lenses and curved mirrors 191–193
 - quasi-optical system components 191
 - solution of approximate wave equation 185–186
 - telescope 188
 - transformation of 186–191
 - truncation of 193–194
- Gaussian beam parameter 190
- Gaussian beam telescope 188
- Gouy phase 56
- grating spectrometer 356–357
- grid constant 300
- group velocity 35
- guided waves 151–199, *See also* circular waveguides; coaxial transmission line; corrugated circular waveguides; Gaussian beams; multimode waveguides; transmission lines; transverse electric (TE) waves; transverse magnetic (TM) waves
- Gunn diode 231
- Gunn oscillator 203–205
 - donation layers 206
 - I/V-characteristic of Gunn diode 206
 - limited space-charge accumulation (LSA) mode 206
 - quenched-domain mode 206
 - typical housing with screwable heat sink 206

h

- half-wave window 197–198
- Hanbury-Brown and Twiss experiment 269
- Hankel function 120
- harmonic mixing 239

- helical field lines 4, 7
 - Helmholtz equation 52, 89
 - Hermitian part of dielectric tensor 23
 - heterodyne detection 236–246
 - diode mixer 239–241
 - mixer construction 245–246
 - square law mixer 237–238
 - two-port mixer 241–244
 - heterodyne radiometers 357–362
 - heterodyne receiver, noise temperature of 253–255
 - high-density polyethylene (HDPE) 192
 - high-pass filter 292
 - hot electron bolometer 225–226
 - hot–cold technique 367
 - hot-plasma dielectric tensor 27
 - hybrid mode 185–194
 - HE_{11} characteristics 185
 - hybrid-factor 184
- i**
- IQ detection 305
 - image frequency 242
 - image port 240
 - image sideband 240
 - imaging reflectometry 348
 - IMPATT oscillator 207–208, 231
 - incoherent detectors 221
 - incoherent scattering 104–106
 - inhomogeneous plasma 48–54
 - inhomogeneous plasma 48
 - in-phase and quadrature signals 304
 - input matching network 245
 - integrated data analysis (IDA) 11
 - intensity interferometer 269–270
 - interferometer 315–326
 - dispersion interferometer 323
 - frequency stability 320–321
 - 2ω -interferometer 323
 - Mach–Zehnder heterodyne interferometer 319–320
 - Mach–Zehnder interferometer 318–319
 - multichannel interferometer 324–326
 - path length variations 322–323
 - swept frequency interferometer 324
 - two-color-interferometer 322
 - wavelength 316–317
 - interferometry 65–70
 - multiple chords 69–70
 - single-chord interferometry 68
 - intermodulation 305–308
 - first-order product 307
 - products of order $|m| + |n|$ 308
 - third-order intercept point 307
 - International Thermonuclear Experimental Reactor (ITER) 7
 - ion cyclotron resonance heating (ICRH) 10
 - ionogram 333
 - isolator 285
- j**
- Joint European Torus (JET) 10
- k**
- Kirchhoff's law 131
- l**
- L-wave 37
 - Larmor formula 103
 - Larmor radius 27
 - Lawson criterion 8
 - lenses 191–193
 - limited space-charge accumulation (LSA) mode 206
 - line-integrated density 68
 - Lithium 3
 - impedance transformation 156
 - localization of reflecting layer 93–94
 - Lorentz force 4, 123
 - lossy transmission line, waves on 151–153
 - low density polyethylene (LDPE) 192
 - lower sideband (LSB) 359
 - low-pass filter 292
- m**
- Mach–Zehnder heterodyne interferometer 319–320
 - magnetic axis 4
 - magnetic plasma
 - confinement 4–10
 - physics issues of 7–9
 - magnetized plasma
 - parallel propagation 37–38
 - perpendicular propagation 39–41
 - magnification 187
 - Martin–Puplett polarizing interferometer 354–356
 - grating spectrometer 357–359
 - Maxwell averaged Gaunt factor 120
 - Maxwell–Boltzmann velocity 128
 - metallic meshes, in band-pass filter 298–300
 - Michelson interferometer 352–354
 - microwave diagnostics 15–16
 - microwave imaging reflectometry (MIR) 350
 - millimeter-wave range, PLL circuits in 309–310
 - millimeter-waves in plasmas 19–62, *See also* cold-plasma dispersion relations

- basic equations 20–23
- derivation within fluid description 32–34
- dispersion relation of the mode 22
- fundamental dispersion relation of waves in plasmas 22
- millisecond time scale 12
- minimum detectable temperature 263–264
- minimum detectable blackbody temperature 263
- mixer construction 245–246
 - input matching network 245
- mixer noise temperature 251–253
- mode coupling 179
- modulation factor 338
- modulation techniques 327–329
 - Scheme 1 327–328
 - Scheme 2 328–329
 - Scheme 3 329
- monolithic microwave-integrated circuits (MMICs) 205
- mono-mode propagation, TE_{11} 180–191
- monostatic arrangement 336
- Müller matrix 327–329
- multichannel interferometer 324–326
- multifrequency systems 332–338
- multimode waveguides 176–181
 - mono-mode propagation, TE_{11} 180–191
 - multimode propagation 178–179
 - number of modes propagating 176–178
- multiple chord interferometry 69–70
- multiple chords, imaging 61–62
- multiplier chain 206–207
- mutual coherence function 267

n

- network-analysis measurement 290–312
 - errors in 290
 - reflection measurement 287–288
 - substitution measurement 288–289
 - transmission measurement 286–287
 - using noise sources 289–290
- neutral beam injection (NBI) 10
- noise-equivalent power (NEP) 226, 260–261
 - coherent detection 261–263
 - incoherent detection 260–261
- noise figure 249–250
- noise sources, measurements using 289–290
- noise temperature 247–249
 - of cascaded systems 250–251
 - of heterodyne receiver 253–255
 - measurement of 255

- mixer noise temperature 251–253
- nonmagnetized plasma 34
- nonreciprocal devices 283–286
- normal dispersion 35
- Nyquist relation 246

o

- odd Matthieu functions 346
- off-axis system 192
- O-mode 42
- ohmic heating 10
- Onsager relation 23
- optical depth 60, 133, 137
- optical depth, in electron cyclotron emission 137–140
- ordinary mode (O-mode) 39
- overmoded circular waveguides, TE_{11} mode in 180–181
- overmoded waveguide, band-pass filter in 295–297
- O–X–B mode conversion 143, 146

p

- passive diagnostics 117–149, *See also*
 - Electron Bernstein wave emission; Electron cyclotron emission
- path length variations 322–323
- phase change at cutoff in reflectometry 75–92
- phase margin 312
- phase measurement 299–304
 - all-digital phase measurement 300–303
 - all-digital phase meter 301
 - with analog output 299–300
 - input signals of 302
 - output signals of 302
 - by software 303–304
- phase memory concept 50
- phase runaway 346
- phased antenna array 218
- phase-locked loop (PLL) 308, 309, 311, 320
 - in millimeter-wave range 309–310
- phase velocity 35
- photoconductor detectors 221
- physics issues of magnetic confinement 7–9
- pitch angle 4
- Planck's law 249
- plasma anisotropy 21
- plasma diagnostic 11–16, *See also* Microwave diagnostics
 - active diagnostics 15
 - generic arrangements 12–15
 - passive diagnostics 15

plasma dielectric tensor 23–25
 – general properties 23–25
 – wave propagation geometry 24
 plasma dispersion function 28
 plasma emitting and absorbing 60–61
 plasma frequency 27
 plasma heating 10
 – heating schemes 10
 plasma pressure 8
 Poincare sphere 79
 polarimeter 326–332
 – modulation techniques 327–329
 – polarization state, evolution 326–327
 polarimetry 70–83
 – Cotton-Mouton effect 75
 – Faraday effect 71–75
 polarization filters 300
 polarization rotator 181–182
 polarization-selective filters 290–299
 polarizing Martin–Puplett interferometer 300
 polytetrafluoroethylene (PTFE) 192
 power coupling coefficient 194
 power range 309
 power wave amplitudes 153
 Poynting vector 124
 profile reconstruction 92–93
 proton-proton-chain (pp-chain) 2
 pulse radar technique 339–342
 pyramidal horn 212–213

q

Q-factor 9
 quenched-domain mode 206

r

R-wave 37
 radiation generation and detection 201–250
 radiation transfer 58–62
 – multiple chords, imaging 61–62
 – plasma emitting and absorbing 60–61
 – transparent plasma 58–60
 radio detection and ranging (RADAR) 15
 ray refractive index 60, 132
 ray tracing 53–54
 Rayleigh–Jeans limit 132, 222, 262
 Rayleigh length 56
 ray refraction 51–53
 realized millimeter-wave diagnostic systems architecture 315–378, *See also*
 interferometer; polarimeter; reflectometer;
 Radiometry of electron cyclotron emission;

Detection of electron Bernstein waves;
 Coherent Thomson scattering
 receiver noise temperature 262
 reciprocal device 277
 rectangular waveguides 163–170
 rectangular waveguides, attenuation in 166–167
 recurrence formula 297
 redundancy 10
 reflection measurement 287–288
 reflectometer 332–348
 – fluctuation measurements 345–346
 – heterodyne version of 358
 – multifrequency systems 332–338
 – ultrashort pulse radar 342–343
 reflectometry 83–100
 – density fluctuations influence 95–100
 – localization of reflecting layer 93–94
 – phase change at cutoff 89–92
 – profile reconstruction 92–93
 – relativistic corrections 95–96
 – time delay measurement 86–87
 refraction 51–53
 refractive index 22
 relativistic corrections 46–48
 relativistic incoherent scattering spectrum 106–107
 return loss 156
 rotational transform 4

s

safety factor 6
 saturation 304–305
 scaling law 9
 scattering 100–115
 – coherent scattering 108–109
 – density fluctuations role 108
 – Doppler shift 102–103
 – electron and ion feature 110–113
 – form factor 104
 – incoherent scattering 104–106
 – parameters 275–277
 – relativistic incoherent scattering spectrum 106–107
 – single-particle Thomson scattering 101–102
 – Thomson scattering 100
 Schottky detector noise 233–236
 Schottky diode 227–229
 – dot matrix Schottky diode 228
 – frequency multiplier 229–231
 Schott–Trubnikov formula 126, 127

- sensitivity limits 256–264
 - bandwidth influence 259–260
 - minimum detectable temperature 263–264
 - noise-equivalent power 260–261
 - coherent detection 263–265
 - incoherent detection 260–261
 - shot noise term 254–257
 - thermal radiation term 259–259
 - shear 4
 - shot noise 256–260
 - signal linearity 304–308
 - gain compression 304–305
 - intermodulation 305–308
 - signal sources 201–207, *See also* Antennas; Correlation radiometry; Detection
 - backward-wave oscillator (BWO) 201–203
 - multiplier chain 206–207
 - solid-state oscillators 203–206, *See also individual entry*
 - single-chord interferometry 68
 - single-disk window 196–197
 - single-particle Thomson scattering 101–102
 - single sideband (SSB) 360
 - single sideband modulation (SSBM) techniques 320
 - slightly oblique propagation 41–42
 - slow X-wave 146
 - ‘smearing out’ effect 353
 - Snell’s law 59
 - software, phase determination by 303–304
 - solid-state oscillators 203–206, *See also* Gunn oscillator; IMPATT oscillator
 - spatial dispersion 28
 - square law mixer 237–238
 - stellarator 6–7
 - Stix geometry 24
 - Stokes equation 89
 - Stokes vector 78, 79, 326
 - stub 157
 - substitution measurement 288–289
 - subsystems 275–313, *See also* Two-port characterization
 - susceptibility 109
 - superconductor–insulator–superconductor (SIS) 239
 - surface currents 160–161
 - sustainable fusion power 3
 - swept frequency interferometer 324
 - swept single-frequency system 333–337
 - bistatic arrangement 334
 - monostatic arrangement 334
 - system impedance 276
 - system noise temperature 255
- t**
- tangential sensitivity 236
 - terminated transmission line 153–157
 - thermal noise 246–255, 264
 - noise temperature 247–249, *See also individual entry*
 - thermal radiation term 258–259
 - thin window 198
 - third-order intercept point 307
 - Thomson scattering 100
 - coherent Thomson scattering (CTS) 106
 - single-particle Thomson scattering 101–102
 - time-of-flight (TOF) measuring system 342
 - tokamak 5–6
 - toroidal field coils 7
 - torus 4–5
 - total power receiver 357
 - transmission lines 151–161
 - classification of 157–159
 - properties 151–161
 - surface currents 160–161
 - terminated transmission line 153–157
 - two-conductor transmission line 152
 - waves on a lossy transmission line 151–153
 - transmission measurement 286–287
 - transparent plasma 58–60
 - transverse electric (TE) waves 159, 164–165, 173–175
 - fundamental TE₁₀-wave 167–170
 - mono-mode propagation, TE₁₁ 180–191
 - TE₁₁ mode in overmoded circular waveguides 180–181
 - transverse electromagnetic (TEM) wave 40
 - transverse magnetic (TM)-waves 40, 166, 172–173
 - triple product 8
 - tritium 3
 - two-color-interferometer 322
 - two-port characterization 275–286
 - directional coupler 281–283
 - nonreciprocal devices 283–286
 - reflection 278–279
 - scattering parameters 275–277
 - transmission 278–281
 - two-port mixer 241–244
 - two-tone test 306
- u**
- ultrashort pulse radar 342–343
 - distance calibration 344–345
 - spurious reflections 344–345

upper hybrid frequency 39
 upper sideband (USB) 358, 361

v

vacuum windows 196–199
 – antireflection coating 198, *See also individual entry*
 – half-wave window 198
 – mounted inside a circular waveguide 197
 – single-disk window 196–197
 – thin window 198
 van Cittert-Zernike theorem 268–269
 varactor multipliers 233
 video bandwidth 235
 visibility depth and localization, in electron cyclotron emission 140
 Vlasov equation 25, 32, 46
 Voigt effect 39
 voltage-controlled oscillator (VCO) 311
 voltage standing wave ratio (VSWR) 156

w

warm plasma approximation 44–46
 wave heating 10
 wave noise 266
 waveguide band-stop filter 294–295
 wavelength 316–317
 waveguide attenuation 393–395
 wave-packet 340
 weakly relativistic model 46
 Wentzel–Kramers–Brioullin (WKB) approximation 49–51
 wire diameter 300

x

X-B mode conversion 143, 146
 X-mode 42

y

Y-factor method 255, 349