

Index

a

- Abbe focometer 890
- Abbe number 645
- absorption 331 ff
 - absorption coefficient 332
 - attenuation coefficient 333
 - Lambert-Beer law 333
 - scattering coefficient 333
 - volume scattering function 333
- accuracy
 - bias 169
 - Hartmann sensor 214
 - Hartmann-Shack sensor 197
 - linearity 169
 - overall variation of a measurement system 170
 - point spread function retrieval 278
 - precision 170
 - repeatability 170
 - reproducibility 170
 - stability 169
 - total system variation 173
- acousto-optic modulator (AOM) 493
- acousto-optic tunable filter 359 ff
 - acoustic angle 493
 - birefringence 363
 - bragg diffraction at acoustic waves 363
 - collinear beam AOTF 360
 - drive power 360
 - index ellipsoid 362
 - interaction length 362
 - non-collinear AOTF 362
 - peak wavelength 363
 - phase matching condition 363
 - polar angle 363
 - response time 369
 - spectral resolution 369
 - transmission 369
 - tuning range 369
- acutance 922
- adjustment 907
- AIAG (Automotive Industry Action Group) 168
- Alvarez lens 756 ff
- analysis of variance method (ANOVA) 172
- angle encoder 524 ff
 - absolute encoder 526
 - accuracy and error sources 527
 - basic principles 527
 - calibration techniques 528
 - incremental angle encoder 526
- angle metrology 524 ff
- angular resolved scattering (ARS) 795 f
- aperture size 901
- atomic force microscope (AFM) 779, 800
 - contact mode (static mode) 802
 - imaging modes 802
 - non-contact mode 803
 - principle technique used in an AFM 801
 - range and resolution of an AFM 804
 - tapping mode (dynamic mode) 803
- autocollimator 528 ff, 910
 - accuracy and error sources 803
 - basic principles 803
 - calibration techniques 532
 - devices 532
- autocorrelation function 939
- axial point spread function 918

b

- beam quality 951 f
- beam-stop 86
- beat frequency 492
- Beer's law 851
- bidirectional reflectance distribution function (BRDF) 166, 795 ff

- bidirectional scatter distribution function (BSDF)
 - noise equivalent BSDF (NEBSDF) 851
- bidirectional scatter distribution function (BSDF) 166, 812 ff
- bidirectional transmittance distribution function (BTDF) 166
- birefringence 664 ff
 - crossed polarizers 166
 - Fizeau interferometer to measure birefringence 671
 - indication of drawing 665
 - ISO 10110 Part 2 665
 - measurement with electronic polarimeter 672
 - metrology 672
 - parallel polarizers 672
 - residual stress-induced birefringence 664
 - rotating polarizers setup 666
 - sample with quadratically rising radial birefringence 666
 - specifications 666
 - tolerances 665
- bubbles and inclusions 673 ff
 - indication of drawing 674
 - ISO 10110 Part 3 674
 - metrology 674
 - setup to inspect bubbles and inclusions 676
 - setup to inspect haze caused by inclusions 677
 - specification of platinum particles 676
 - specifications 676
- c**
- capability of measurement systems 168
- carrier-envelope offset frequency (CEO) 505
- caustic 35
- cavity length 28
- ceiling, relative 926
- centering 760 ff, 910 ff, 202
 - adjustment of lens support 28
 - centering errors 28
 - centering errors of Hartmann-Shack sensor 202
 - centering errors of point spread function retrieval 265
 - centering metrology for aspherical lens elements 28
 - centering metrology with adjusted lens support 28
 - centering metrology with unadjusted lens support 28
 - critical points in centering metrology 28
 - datum axis 760
 - datum point 760
 - indication of drawings 763
 - inner and outer centering 762
 - lateral displacement of an aspherical surface 761
 - lateral displacement of an optical element or subsystem 761
 - metrology 761
 - optical axis 760
 - tilt angle of a spherical surface 760
 - tilt angle of an aspherical surface 760
 - tilt angle of an optical element 761
- central thickness 689 ff, 907 ff
 - interferometric measurement using short coherent light 761
- measurement by contacting (Abbe method) 761
- measurement using optical proximity sensors 691
- measurement using two chromatical confocal sensors 691
- metrology 691
- optical measurement from one side 692
- specification 689
- cesium atomic clock 505
- chamfer metrology 776 ff
- Chebyshev polynomials 702 ff
- chromatical aberrations 929
- coatings 839 ff
 - abrasion resistance 846
 - absorptance metrology 846
 - adhesion 846
 - area imperfections 847
 - back-surface reflection 867
 - back-surface reflection suppression 867
 - band-stop 841
 - characteristics of an AR multi-layer coating 841
 - coating tolerance 846
 - cross-hatch resistance 846
 - data analysis 846
 - definition of coatings by function. 846
 - detector surface reflection 864
 - diffuse interface 864
 - graded interfaces 864
 - integrating sphere setup 864
 - ISO 9211-4 846
 - laser calorimetry arrangement 877
 - line-like imperfections 847
 - Magnesium Fluoride MgF₂ 841
 - material designation 841

- metrology 841
- monochromatic unpolarized photometer setup 859
- photothermal effect 877
- point-like imperfections 847
- quarter-wave system 841
- reflectance metrology 841
- solubility 846
- specification 846
- spectral absorptance 846
- spectral photometer or polarimeter arrangement 846
- spectral polarized photometer setup 860
- spectral reflectance 860
- spectral scatter 845
- spectral transmittance 845
- stationary Helmholtz equation 849
- surface roughness 854
- Tantalum Pentoxide Ta₂O₅ 841
- total transfer matrix 850
- transfer-matrix method 850
- transition matrix 850
- transmittance metrology 850
- transmittance of plane-parallel elements 850
- V-N setup 850
- volume imperfections 847
- V-W setup 871
- coefficients of thermal expansion (CTE) 153
- coherence
 - coherence function 19
 - coherence length 19
 - coherence time 19
 - correlation function 19
 - partial coherence in Hartmann sensor 216
- colored glass filter
 - band-pass filter 19
 - edge wavelength 345
 - internal transmission 344
 - Limit of blocking range 344
 - Limit of pass range 346
 - long-pass filter 345
 - luminescence 348
 - short-pass filter 345
 - solarization 348
 - temperature influence on colored glass filters 348
- combined distance and Aagle metrology 540 ff
- compensator 589 ff
 - Babinet compensator 348
 - Babinet-Soleil compensator 348
 - photoelastic modulator (PEM) 590
- compensator plate 56 ff
- complex numbers 8
- computer-generated hologram (CGH) 122, 729 ff
 - amplitude grating 8
 - calculating the structures of a CGH 8
 - CGH with ring-shaped focus control zone 740
 - deflection angle as a function of groove density 733
 - groove depth 731
 - Littrow angle as a function of groove density 734
 - Littrow arrangement 733
 - local grating period 732
 - maximum grating density in a CGH 740
 - off-axis CGH as a null corrector 734
 - phase grating 734
 - theoretical diffraction efficiencies 732
- confocal sensor 517 ff, 892
 - chromatic confocal sensor 122
 - coaxial interferometric sensor 122
 - monochromatic confocal sensor 122
- conic surface with elliptical principal sections 752 ff
- contrast 897
- corner cube 493 ff
- criterion 893
 - focus 893 f
 - Hopkins 941
 - MTF 941
 - SQF 942
 - Thomas 920
- d**
- dead path 497
- deflectometer 432, 890
 - accuracy and error sources 497
 - algorithms 469
 - basic setups 469
 - calibration 469
 - deflectometer to test mirrors 467
 - deflectometer to test strongly curved surfaces 468
 - geometric parameters for a deflectometer 466
 - resolution 471
 - to test transmissive test samples 465
- depolarization 560, 572
- depolarizer 591 ff
 - Cornu depolarizer 572
 - Lyot depolarizer 592
 - quartz-silica wedge depolarizer 592

- detection of flux 338 ff
 - light guide value 592
- diameter metrology 776 ff
- diattenuation 560, 957
 - of tilted glass plates 574
- dispersion-free material 22
- displacement metrology
 - absolute displacement-measuring Interferometer 22
 - short-range 22
 - thickness 22
 - to measure the tilt of a plane mirror 22
- distortion metrology
 - accuracy and error sources 22
 - basic setups 22
 - calibration 463
 - correlation masks 463
 - correlation method 463
 - cross-correlation 463
 - dynamic range 463
 - Moiré technique 463
 - of systems 929
 - sinusoidal masks 463
- Doppler effect 19
- Doppler shift 492
- double-frequency grating 80
- Duffieux integral 939
- dynamometer 902
- dynamic range
 - improvements 143
 - improvements 143
 - in surface topometry 140
 - lateral dynamic range 143
 - lateral resolution 143
 - limitations 143
 - maximum fringe density 142
 - of Hartmann-Shack sensor 194
 - using a single point detector 141
- e**
- edge 230, 688, 917 f, 932
 - defect 922
 - displacement 928
 - measurement 917
 - model function 935
 - steepness 921
 - width 920
- edge spread function 919 f, 933
- Edlén formula 153
- electro-optic effect 587 ff
- elementary beam of radiation 323 f
- ellipsometer 622 ff
 - accuracy and error sources 153
 - calibration techniques 153
 - null ellipsometer 629
 - PCm SAR arrangement 631
 - PCmSA arrangement 634
 - PCrSCr A arrangement 633
 - Pr SA arrangement 633
 - PrCSA arrangement 633
 - PSCmA arrangement 634
 - PSCrA arrangement 632
 - rotating analyzer ellipsometer (RAE) 632
 - spectroscopic ellipsometer 632
 - systematic errors 636
 - to measure complex reflectivities 628
- encircled energy (EE) 443, 917
- energy of radiation 305 ff
 - electric field strength 306
 - dielectricity 306
 - electromagnetic field 306
 - energy density 306
 - irradiance 308
 - magnetic field strength 306
 - magnetic permeability 306
 - phase velocity 307
 - Poynting vector 307
 - refraction index 307
 - wave vector 306
- entropy 897
- envelope detection 502
- environmental limitations 496
- error sources
 - Abbe error 62
 - acoustics 160
 - air turbulence 496
 - conduction 159
 - convection 157
 - cosine error 157
 - dark current noise 162
 - data age uncertainty 499
 - environmental noise 167
 - erroneous reflections 167
 - figure error of the mirror surface 497
 - fixed-pattern noise 162
 - Hartmann-Shack sensor 195
 - imperfect components 497
 - imperfections in AR-coatings 497
 - instrument errors 499
 - misalignment of components 498
 - overlap error 498
 - polarization leakage error 497
 - radiation 158
 - readout noise 162
 - sound 160
 - thermal stability 153

- transfer noise 162
 - vibrations 149
- ESF 919 f

f

- F-number 51
- Fabry-Pérot resonator 37
- Fabry-Pérot-etalon 349 ff
- finesse 37
 - free spectral range 350
 - FWHM 350
 - multiple Fabry-Pérot-etalon 350
 - spectral resolution 351
 - tuning Fabry-Pérot-etalon 352
- Faraday effect 588
- femtosecond frequency combs 504
- femtosecond pulse laser 504
- five-sample-adaptive algorithm (FSA) 502
- Fizeau interferferometer 49
- Fizeau surface 49, 122
- focal length 887 ff
- focimeter 889
- focometer 890
- focus criterion 893
- Foucault test 230 f, 688, 917 f
- Fourier spectrometer 411 ff
- spatially modulated Fourier spectrometer 51
 - spectral resolution 51
 - temporally modulated Fourier spectrometer 51
- Fresnel equations 37, 39
- fringe analysis
- asymmetric kernel 101
 - Carré algorithm 107
 - convolution kernel 101
 - detuning error 101
 - discrete convolution 101
 - erroneous fringes 101
 - error sources 97
 - Gaussian window 99
 - indicator function 116
 - lateral resolution 116
 - least-squares phase detection 95
 - least-squares procedure 95
 - multi-fringe interferogram 108
 - nonlinearity error 105
 - phase-shifting interferometry 98
 - simultaneous phase-shifting interferometry 112
 - spatial carrier frequency analysis 107
 - statistical phase fluctuations 107
 - synchronous detection 107

- Takeda algorithm 108
 - two-dimensional convolution kernel 110
 - unwrapped phase 115
 - unwrapping 115
 - unwrapping in the presence of noise 118
 - von Hann window 99
 - window function 99
 - wrapped phase 115
- fringes
- bright fringes 115
 - concentric circular interference rings 41
 - dark fringes 41
 - fluffing fringe contrast 23
 - fringe contrast 16
 - fringe profile 16
 - fringe spacing 16
 - fringe visibility 16
 - Haidinger fringes 16
 - Newton fringes 16
 - of equal inclination 16
 - of equal thickness 16
 - of two waves with different wavelengths 18
 - sinusoidal shape 18
 - straight parallel and equally spaced 18
- full-well capacity 163
- fundamental law of radiometry 321 ff

g

- Gauge capability ratio (GCR) 175
- Gauge R&R analysis 170
- Gauss method 888
- Gaussian irradiance profile 85
- Gaussian oscillator 852
- geometry of optical components 679 ff
- Gerchberg-Saxton 270 f
- ghost image 950
- glare index 950
- glare spread function 950
- goniometer spectrometer
- Abbe arrangement 650
- goniometer spectrometer 647 ff
- grating image 936
- grating monochromator 387 ff
- angular dispersion 650
 - blazed diffraction grating 650
 - concave grating monochromator 650
 - configurations of grating monochromators 650
 - constant deflection angle 650
 - Czerny-Turner monochromator 400
 - diffraction at gratings 400
 - diffraction efficiency 395

- Fastie-Ebert monochromator 395
- free spectral range 395
- grating equation 388
- linear dispersion 397
- resolving power 397
- spectral bandwidth 398
- spectral resolution 398
- throughput 398

h

- harmonic oscillator 852
- Hartmann sensor 208 ff
 - accuracy 214
 - apodization 218
 - partial coherence 216
- Hartmann-Shack sensor 183 ff
 - averaging 197
 - calibration 204
 - centering error 202
 - cross-talk 195
 - diameter adaptation 189
 - dynamic range 194
 - error sources 195
 - layout 192
 - relay lens 190
 - setup 187
- Height Transfer Function 112
- Hindle test 132 ff
- holographic modal sensor 240
- Hopkins factor 941
- Huygens' principle 34, 37

i

- IFTA 270 f
- illumination 948
- image
 - contrast 931
 - degradation 926
 - gradient 895, 897
 - quality 912 ff, 941
- image analysis 432 ff, 912 ff
 - calibration principles 435
 - mask-projecting system 433
 - performance criteria 912 ff
 - system setup 432
- image gradient 895, 897
- image location 892 f
- image quality 912 ff
- infinite series 38, 40
- inhomogeneity 655 ff
 - Fizeau interferometer to measure inhomogeneity 432
 - indication of drawing 657

- ISO 10110 Part 4 656
- measurement at polished samples 660
- measurement in immersion tank 661
- metrology 661
- oil-on-plates sandwich method 661
- specification 656
- integrating sphere 821, 946
- intensity moments 915
- interface-radiation through 324 ff
 - Fresnel equations 656
 - polarization 326
 - reflectivity 326
 - transmissivity 326
- interference
 - contrast 19
 - of non-spherical wavefronts 33
 - of two monochromatic waves with statistically phase 20
 - of two plane waves 12
 - of two spherical waves 14
 - of two waves which have a spectrum 21
 - of waves having different polarization 31
 - with extended monochromatic light sources 27
- interference filter 352 ff
 - all-dielectric interference filter 27
 - central wavelength 357
 - circular wedge filters 357
 - effective refraction index 356
 - FWHM 357
 - linear wedge filters 357
 - peak transmission wavelength 354
 - thermo-optic tuning 358
- interference microscope 804 ff
 - differential interference contrast microscope (DIC) 358
 - examples of interference microscope objectives 806
 - for very rough surfaces 811
 - Linnik interference microscope 807
 - Michelson objective 807
 - Mirau objective 807
 - Nomarski arrangement 807
 - reference-free interference microscope 807
- interferometer
 - absolute displacement-measuring interferometer 807
 - accuracy 807
 - common-path 44
 - compensating system 121
 - cyclic Interferometer 121

- displacement-measuring interferometer 121
- double-pass 121
- environmental limitations 148
- equal-path 44
- error sources 44
- Fizeau interferometer 49
- grating angle shearing interferometer 78
- heterodyne 491
- homodyne 491
- Jamin interferometer 491
- lateral-shear 44
- low-coherence 44
- Mach-Zehnder interferometer 44
- mechanical stability 149
- Michelson interferometer 149
- multiple-beam 44
- multiple-pass 44
- Newton interferometer 44
- null-system 121
- point diffraction interferometer (PDI) 121
- radial-shear 44
- reversal-shear 44
- rotational-shear 44
- shearing interferometer 44
- single-pass 44
- Smartt interferometer 44, 235
- two-beam 44
- Twyman-Green interferometer 44
- unequal-path 44
- Williams interferometer 60
- interferometer calibration
 - averaging of non-rotationally symmetric errors 126
 - ball averaging 131
 - calibration of non-rotationally symmetric errors 124
 - calibration procedures to determine element deviations 122
 - calibration techniques 120
 - cat's eye position 123
 - deviation of a reference element 121
 - liquid surface 121
 - non-rotationally symmetric deviations 124
 - reference elements with known residual error 121
 - retrace error of an interferometer 121
 - rotating sphere 131
 - rotationally symmetric deviations 124
 - shift-rotation technique 125
 - three-flat test 128
 - three-flat test extended to spherical surfaces 129

- three-position technique 122
- well-known reference surface 121
- interferometer design
 - beam expansion 85
 - bulls eye 93
 - distortion 91
 - field curvature 89
 - holographic optical element 94
 - lateral resolution 86
 - reduction of coherent artefacts 91
 - rotating diffuser disk 93
- internal transmittance 335
- optical density 335
- ISO standard 885

j

- Jamin interferometer 491
- Jones calculus 561 ff, 956
- Jones matrix 563 ff
 - determination from measured Jones vectors 567
 - for different polarizing elements 566
 - measurement of the Jones matrix 566
 - of selected optical components 566
- Jones pupil 956
- Jones vector 561
 - measurement of Jones vector 566
 - measurement with compensator and rotating polarizer 599

k

- Kepler-type telescope 58, 63
- Kerr effect 588
- knife edge method (Foucault test) 230, 688, 917 f, 932
- kurtosis 954

l

- Lambertian radiator 321
- Larkin, Kieran 502
- laser tracker 544 ff
 - accuracy and error sources 502
 - basic principles 545
 - calibration techniques 547
 - devices 547
- lens position 907
- line spread function 919, 923 ff, 936
- linear encoder
 - absolute type 514
 - accuracy and error sources 514
 - calibration techniques 515
 - diffraction scale encoder 513
 - hologram scale encoder 513

- incremental type 513
 - Moiré method 512
 - reference mark 513
 - liquid crystal polarization grating 374 f
 - free spectral range 513
 - spectral resolution 513
 - tuning range 513
 - liquid crystal tunable filter 369 ff
 - free spectral range 373
 - FWHM 373
 - Lyot-Ohman filter 373
 - response time 373
 - spectral resolution 373
 - tuning range 373
 - Lorentz oscillator 852
 - LSF 919, 923 ff, 936
 - Lyot test 235
 - Löber, August 45
- m**
- M2 951 f
 - Mach, Ernst 62
 - Mach-Zehnder interferometer 44
 - magneto-optic effect 587 ff
 - magnification 900 f
 - Maltese cross 957
 - manufacturing specifications 886
 - matt surface 787
 - Maxwell's equations 4
 - mean radial profile 706 f
 - measurement system analysis (MSA) 168
 - Michelson, Albert 56
 - Michelson interferometer 149
 - microdefects 787
 - microlens array 183
 - microscope lens 904
 - minimum deflection angle of a prism 648
 - modal method 285
 - modulation transfer function 930 ff
 - moiré deflectometry 890
 - moments of intensity 915
 - monochromatic wave 7
 - monochromator 341 f
 - absorption filter 7
 - colored glass filter 7
 - mount techniques for optical elements 710 f
 - three-ball mount to support lens elements 712
 - Mueller matrix 570, 959
 - measurement of complete Mueller matrix 712
 - measurement of Mueller matrix elements 712

- of selected optical components 712
- of systems 954

n

- Newton interferometer 44
- noise
 - CCD Noise Sources 162
- non-ambiguity range 507
- null corrector 727 ff
 - in a Fizeau interferometer 728
- matrix system in a Fizeau interferometer 728
- null-system of interferometers 121
- Nyquist limit 86 f, 112, 142

o

- OCT 908
- oil plates 54
- optical profile metrology 548 ff
 - accuracy and error sources 550, 554
 - calibration techniques 550, 555
 - CMM with optical sensors 555
 - deflectometry 555
 - devices using angle sensors 555
 - extended shear angle difference method (ESAD) 555
 - long trace profiler (LTP) 555
 - multiple-distance sensor module (MDS) 555
 - setup to measure optical freeform surfaces 549
 - traceable multi-sensor technique (TMS) 549
- optical transfer function (OTF) 443, 930 ff
- OTF 443, 930 ff

p

- pattern and fringe projectors
 - accuracy and error sources 443
 - algorithms 479
 - basic setups 471
 - calibration 479
 - calibration plate with well-known fiducials 482
 - central projection 475
 - intrinsic and extrinsic parameters 480
 - invisible regions 477
 - pattern projection 477
 - photogrammetry 478
 - resolution 484
 - Scheimpflug condition 476
 - telecentric projection 474
 - triangulation 474

- pattern projection 432
- performance specifications 886
- phase retrieval 249 ff
 - accuracy 278
 - algorithms 270
 - apodization 274
 - centering 265
 - illumination 254
 - image processing 262
 - model 258
 - object space defocusing 275
 - principle 251
 - pinhole deconvolution 267
 - setup 253
- phase space analyzer 219 ff
 - layout 222
 - wave optical description 227
- phase-stabilized frequency comb 505
- photometric quantities 314 ff
 - v -lambda function 315
 - aqueous humour 314
 - candela 314
 - CIE standard photometric observer 316
 - cones 316
 - cornea 314
 - eye 314
 - iris 314
 - mesopic vision 315
 - photopic vision 315
 - retina 314
 - rods 314
 - scotopic vision 315
 - spectral luminous efficacy of radiation 316
 - vitreous humour 314
- plane parallel plate – transmittance through 335 ff
- plane wave 6
- planotonic or cylindrical surface 751
- point diffraction interferometer (PDI) 121
- point diffraction plate 67 ff
- point image filtering 230 f
- point spread function (PSF) 443 ff, 914 ff
 - axial 918
 - intensity moments 915
 - phase retrieval 249 ff
 - Strehl ratio 915 f
- polarimeter 605 ff, 622 ff
 - complete/incomplete Mueller polarimeter 622
 - dual-PEM setup PCmSCmA 627
 - PCmSA arrangement 627
 - PCrSCrA arrangement 627
 - PrCSA arrangement 627
 - PrSA arrangement 627
 - PrSAr arrangement 627
 - PSrA arrangement 627
 - used to measure birefringence 622
 - using PEMs 622
- polarization
 - aberrations 954
 - by reflection 573
 - birefringent polarizer 575
 - dichroic polarizer 575
 - Glan-Foucault prism 575
 - Glan-Taylor prism 575
 - Glan-Thompson prism 575
 - Nicol prism 576
 - of systems 954
 - of tilted glass plates 573
 - polarizing beam-splitter cubes 576
 - Rochon prism 576
 - thin-film or interference polarizer 579
 - wire-grid polarizer 579
 - Wollaston prism 579
- polarizer 572 ff
 - polarizing beam-splitter 574 f
- polarizing elements 572 ff
- power in the bucket 917
- power spectral density (PSD) 789 ff
 - 1D power spectral density function 790
 - 2D power spectral density function 790
 - 2D-isotropic PSD 790
- precision to tolerance ratio P/T 175
- principal planes 898
- prism monochromator 375 ff
 - Abbe prism 175
 - angular dispersion 175
 - constant deflection by a dispersion prism 175
 - deflection by a prism 175
 - dispersion 383
 - linear dispersion 383
 - minimum deflection of a dispersion prism 383
 - Pellin-Broca prism 379
 - resolving power 379
 - spectral bandwidth 384
 - spectral resolution 384
 - throughput 384
 - Wadsworth arrangement 378
- PSD 789 ff
- PSF 443 ff, 914 ff
- pupil location 901
- pyramid curvature sensor 239

q

- quantum characteristics of radiation 319 f
 - actinometry 319
 - Avogadro number 320
 - dose 320
 - Einstein 320
 - electron volt 320
 - photon 320
 - Planck's constant 319

r

- radiance invariance 324
- radiometric quantities 309 ff
 - irradiance 309
 - projection of irradiance 310
 - radiance 310
 - radiant energy 312
 - radiant exitance 310
 - radiant exposure 312
 - radiant flux 309
 - radiant intensity 309
 - radiant power 309
 - solid angle 309
 - spectral radiometric quantities 314
- radius of curvature 681 ff
 - as a function of temperature 688
 - bar spherometer 685
 - deflectometry 688
 - error sources 687
 - Foucault test (knife-edge test) 230, 688, 917 f
 - interferometry against a plane reference surface 688
 - ISO 10110 Part 5 681
 - metrology 681
 - relative radius error 685
 - sagitta error 681
 - specification 681
 - spherometer 683
 - test-glass method 683
 - test-glass method in a Fizeau interferometer 683
 - three-leg spherometer 683
 - total surface deviation function 681
 - traveling microscope method 688
 - two-position test 688
- Rayleigh criterion 30
- refractive index
 - immersion compensation 647
 - metrology 647
 - of the prism 648
 - specification 645
 - subscripts for associated wavelength 645

- tolerances 646
- relative ceiling 926
- retardance 560, 957
- retarder 582 ff
 - circular retarder 560
 - Fresnel double rhomb 585
 - Fresnel rhomb 585
 - half-waveplate 583
 - linear retarder 583
 - optically active component 587
 - Pockels cell 587
 - quarter-waveplate 583
 - rhomb 583
 - waveplate 583
- Ritchey-Common test
 - in different angular positions 583
 - with a circular-shaped mirror under test 583
 - with a non-circular-shaped mirror under test 583
- Ronchi grating 890, 894, 903
- Ronchi test 230 f
- rotationally symmetric aspherical surfaces 735 ff

s

- scanning probe microscopy (SPM) 800 ff
 - characteristics of SPMs 583
 - SPM for large samples 802
- scanning tunneling microscopy (STM) 800
- scattering by optical surfaces 794 ff
- scatterometer 812 ff
 - ARS scatterometer 800
 - ASTM standard for TIS 818
 - backward scatter TIS measurement 818
 - BSDF scatterometer 818
 - calibration 816
 - Coblenz sphere 816
 - forward scatter TIS measurement 819
 - integrating sphere factor M 819
 - near specular geometry 815
 - receiver unit configuration 814
 - signature of BSDF scatterometer 815
 - TIS scatterometer 817
 - TS and TIS measurement with integrating sphere 821
 - Ulbricht sphere (integrating sphere) 821
- second-order surface 751
- Sellmeier equation 646
- Senarmont method 623 f
- shearing interferometer 44
- shear plate 77
- signal-to-noise ratio (S/N or SNR) 162 f

- slope measurement 287
- Smartt interferometer 235
- Sommargren, Gary 70
- specific OPD changes 156
- specifications 884
 - manufacturing 886
 - of optical materials 644 ff
 - performance 886
- speckle effects 165
- spectral transmission 947
- spectrometer 402 ff
 - calibration of wavelength scale 165
 - calibration of radiant flux 165
 - chopper 406
 - detection monochromator 404
 - double-beam spectrometer 404
 - illumination monochromator 403
 - multi-channel device 403
 - multi-channel spectrometer 403
 - photometric accuracy 403
 - single channel device 403
 - single-beam spectrometer 405
 - single-channel spectrometer 405
 - spectral reflectance 404
 - spectral resolution of multichannel spectrometers 409
 - spectral transmittance 404
 - spectrophotometer 402
 - spectroradiometer 402
 - wavelength accuracy 420
- specular surface 787
- spherical wave 8, 14
- SQF criterion 942
- star test, slit test 442 ff, 787 f, 914 ff, 923 ff
 - accuracy and error sources 787
 - Airy pattern 787
 - annular aperture 437
 - array of point sources 442
 - calibration 442
 - dimensions of star mask 442
 - image deconvolution 443
 - star image irradiance distribution 443
 - to test afocal systems 443
- steepness 921
- stitching technique 145 ff
- Stokes vector 568 ff
 - measurement of Stokes vector 443
 - measurement of Stokes vector using PEM and polarizer 443
- Stokes/Mueller calculus 568 ff
- stray light 50 ff, 86, 950
- Strehl ratio 915 f
- striae 655 ff
 - indication of drawing 657
 - ISO 10110 Part 4 657
 - metrology 657
 - shadowgraph image simulation 664
 - shadowgraph setup 664
 - specification 657
 - striae model 657
- structural content 944
- Struve ratio 925
- super luminescent diode (SLD) 503
- surface form and figure irregularities 694 ff
 - Alvarez lens to test second-order and toric surfaces 757
 - approximating aspherical surface 695
 - approximating spherical surface 695
 - concentric lens elements 695
 - D/R-diagram for transmission spheres 721
 - decomposition 698
 - effective reference surface 698
 - environmental conditions 712
 - finite element method (FEM) 709
 - Fizeau surface 719
 - geometrical parameters for ring-zone testing of aspheres 749
 - gravity and orientation 749
 - horizontal interferometer and a vertical test beam 711
 - horizontal interferometric setup 710
 - indication of drawing 697
 - interferograms for surfaces using transmission sphere 723
 - interferometer using short coherent light to test 716
 - interferometric setup to test aspherical back surfaces 742
 - irregularity 695
 - irregularity function 695
 - ISO 10110 Part 5 694
 - limitations for surfaces to test by transmission sphere 720
 - local retrace error 747
 - metrology 747
 - misalignment when testing surfaces 747
 - misalignments of spherical surfaces 747
 - oblique incidence interferometer by means of a prism 718
 - peak-to-valley (PV) difference 695
 - principal surface of a transmission sphere 695
 - productivity 695
 - retrace error compensation 747
 - ring-zone testing 747

- rms asymmetry, RMSa 696
 - rms irregularity, RMSi 696
 - rotationally symmetric irregularity 695
 - sagitta error 695
 - specification 695
 - spherical lens elements with problematic geometry 726
 - spurious reflections 714
 - subaperture testing 714
 - surface-form deviation 694
 - surface-form measuring interferometers 694
 - test tower arrangement 724
 - testing freeform surfaces 724
 - testing generalized second-order and toric surfaces 724
 - testing in oblique incidence 717
 - testing plane surfaces 717
 - testing rotationally symmetric aspherical surfaces 717
 - testing surfaces with full compensation 755
 - testing surfaces with partial compensation 759
 - testing surfaces with refractive null systems 759
 - testing spherical surfaces 759
 - testing with diffractive null systems (CGHs) 759
 - testing with fully compensated setup 759
 - testing with partially compensated 759
 - testing with refractive null systems 759
 - total rms deviation, RMSt 695
 - total surface deviation function 695
 - transmission spheres 695
 - uncompensated testing 695
 - uncompensated testing of surfaces 759
 - various null systems to measure aspherical surfaces 737
 - wavefront error function 698
 - surface imperfections 823 ff
 - analogue microscope image comparator (MIC) 698
 - bright-field detector 828
 - comparison of methods I and II 835
 - dark-field detector 829
 - indication in drawings 829
 - inspection using a stray-light sensor 830
 - inspection using an integrating sphere (method II) 830
 - metrology 830
 - obscured or affected area method (method I) 830
 - size designation for surface imperfections 824
 - specification 824
 - visibility class designations 826
 - visibility method (method II) 823
 - surface texture 785 ff
 - band limited roughness 790
 - bandwidths of texture measuring instruments 797
 - grade numbers, permissible number of microdefects 793
 - indication in drawings 793
 - metrology 793
 - microdefects 793
 - power spectral density (PSD) 793
 - specification 793
 - surface roughness R_q 793
 - surface waviness 793
 - tactile profilometer 793
 - typical parameters of tactile profilometers 799
 - system performance 883
- t**
- tabletop compliance 152
 - Talbot effect 244 f, 891
 - telecentricity 905 f
 - Tenengrad 895
 - test glass 45 ff
 - test pattern 432 ff, 543 ff, 932
 - accuracy and error sources 543
 - amplitude modulation 543
 - basic principles 543
 - calibration techniques 544
 - checkerboard 152
 - chirped circular grid 434
 - chirped linear grid 434
 - circular spot grid 434
 - concentric equidistant rings 434
 - devices 544
 - polarization modulation 543
 - random pattern 434
 - rings and spokes 433
 - Siemens star 434
 - single circular spot 433
 - single slit 433
 - time-of-flight 541
 - uniform equidistant grid 433
 - USAF target 433
 - theodolite and total station 541 ff
 - thermal coefficients of different materials 154
 - Thomas criterion 920

Ti:sapphire (titanium-sapphire) laser 505 ff
 tilt metrology 524 ff, 910 ff
 – accuracy and error sources 154
 – calibration techniques 534
 – differential heterodyne laser interferometer 534
 – displacement-measuring interferometer 534
 – surface-measuring interferometer 534
 time-of-flight measurement 505 ff
 toric surface 752 ff
 toroidal lens 221
 total integrated scatter (TIS) 795 f
 total internal reflection 904
 total scatter (TS) 795 f
 transfer function 930 ff
 transmission 945 f
 transmission flat 53, 85, 128, 714 ff
 transmission sphere 49 ff, 719 ff
 transmittance
 – absorption coefficient 654
 – internal transmittance 654
 – metrology 654
 – of systems 945 f
 – photochromic sample 655
 – reflection factor 651
 – specification 651
 – spectral photometer 654
 – transmittance photometer light sources 653
 transport of intensity equation 249
 triangulation 432

triangulator 515 ff
 tunable repetition rate 509
 Twyman-Green interferometer 44

V

V-edge surface 752 ff
 vector perturbation theories (VPT) 796
 veiling glare 950
 Verdet constant 588
 vertex position 909
 vibration specifications 150
 vibration-isolation system 149 ff
 vignetting 948
 visual inspection 450

W

wavefront 912
 wavefront sensor 183 ff
 Williams interferometer 60
 wire test 230 f
 Wolter test 235

Z

Zehnder, Ludwig 62
 Zeiss, Carl 45
 Zernike polynomials 283 ff, 288 ff, 699 ff, 894, 959
 – calculation 288
 – normalization radius 291
 – propagation 292
 Zernike test 235
 zonal method 284

